

BBBBBBBBBBBB		000000000		000000000		TTTTTTTTTTTT		SSSSSSSSSS
BBBBBBBBBBBB		000000000		000000000		TTTTTTTTTTTT		SSSSSSSSSS
BBBBBBBBBBBB		000000000		000000000		TTTTTTTTTTTT		SSSSSSSSSS
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000000000		000000000		TTT	SSSSSSSSSS	
BBBBBBBBBBBB		000000000		000000000		TTT	SSSSSSSSSS	
BBBBBBBBBBBB		000000000		000000000		TTT	SSSSSSSSSS	

[illegible]



SYSGEN  
Table of contents

K 5  
- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00

Page 0

(1)	351	BOO\$USEFILE - Use parameter file
(1)	434	BOO\$USEACT - Use active parameters
(2)	459	BOO\$WRTACT - Write parameters to system
(3)	522	BOO\$WRTCUR - Write Current Parameters
(4)	558	BOO\$SENDOPER - Output facility error message to operator
(4)	602	BOO\$CONFIGALL - Auto-configure all adapters
(4)	797	AUTOLOG - AUTO ALL /LOG formatting
(4)	844	SGN\$GET_DEVICE - Locate device database
(4)	944	Reset routines BOO\$RESETLIST and BOO\$CONRESET and BOO\$MSCP_RESET
(4)	1030	BOO\$CONADP - Set connect adapter number
(4)	1154	BOO\$CONNECT - Connect specified device and load driver
(4)	1337	BOO\$LOAD - Load a driver or misc code if not already loaded
(4)	1346	BOO\$RELOAD - Reload a specified driver
(4)	1431	BOO\$GIVEHELP - Print Help information

```

0000 1      .IF      NDF,CONFIGSW
0000 2      .TITLE   SYSGEN - SYSGEN UTILITY AND PARAMETER FILE EDITOR
0000 3      .IFF
0000 4      .TITLE   CONFIGUTL - SYSGEN UTILITIES FOR CONFIGURE PROCESS
0000 5      .ENDC
0000 6      .IDENT   'V04-002'
0000 7
0000 8 *****
0000 9
0000 10  *  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 11  *  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 12  *  ALL RIGHTS RESERVED.
0000 13
0000 14  *  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 15  *  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 16  *  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 17  *  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 18  *  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 19  *  TRANSFERRED.
0000 20
0000 21  *  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 22  *  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 23  *  CORPORATION.
0000 24
0000 25  *  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 26  *  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 27
0000 28 *****
0000 29
0000 30
0000 31  ++
0000 32
0000 33  Facility: System generation and initialization
0000 34
0000 35  Abstract: SYSGEN is the main routine to provide all SYSBOOT parameter
0000 36  alteration commands in an online environment.
0000 37
0000 38  Environment:
0000 39
0000 40  Author: RICHARD I. HUSTVEDT, Creation date: 4-MAY-1978
0000 41
0000 42  MODIFIED BY:
0000 43
0000 44  V04-002 WHM0011      Bill Matthews      14-Sep-1984
0000 45  Changed the defaults for the MSCP command.
0000 46
0000 47  V04-C01 WHM0010      Bill Matthews      04-Sep-1984
0000 48  Changed IO PRIORITY default for the MSCP command and
0000 49  disallow loading of the MSCP server multiple times.
0000 50
0000 51  V03-023 WHM0009      Bill Matthews      23-Jul-1984
0000 52  Changed defaults for the MSCP command.
0000 53
0000 54  V03-022 WHM0008      Bill Matthews      20-Apr-1984
0000 55  Removed WRITE CURRENT code that wrote the SYSGEN parameters
0000 56  to SYS.EXE.
0000 57

```



0000	58	:	V03-021	WHM0007	Bill Matthews	04-Apr-1984
0000	59	:			Added support to write current to write to a seperate	
0000	60	:			default system parameter file.	
0000	61	:			Added support to use file to accept long ascii sysgen parameters	
0000	62	:				
0000	63	:	V03-020	WHM0006	Bill Matthews	14-Mar-1984
0000	64	:			Modify SGN\$GET_DEVICE to take out the I/O database MUTEX and	
0000	65	:			raise IPL before calling IOC\$SEARCHALL.	
0000	66	:				
0000	67	:	V03-019	WHM0005	Bill Matthews	13-Mar-1984
0000	68	:			Move definition of BOO\$GL_LOAD_ARGS from SYSBOOCMD to	
0000	69	:			this module.	
0000	70	:				
0000	71	:	V03-018	ACG0399	Andrew C. Goldstein,	10-Mar-1984 0:36
0000	72	:			Change check for SS\$ NODEVAVL to SS\$_NOSUCHDEV due to	
0000	73	:			rewrite of IOC\$SEARCHDEV.	
0000	74	:				
0000	75	:	V03-016	WHM0004	Bill Matthews	23-Feb-1984
0000	76	:			Added support for loading and starting the MSCP server.	
0000	77	:				
0000	78	:	V03-015	WHM0003	Bill Matthews	04-Feb-1984
0000	79	:			Added support for ACF\$B_COMBO_VECTOR_OFFSET to clean up support	
0000	80	:			of combo style devices.	
0000	81	:				
0000	82	:	V03-014	TMK0001	Todd M. Katz	31-Jan-1984
0000	83	:			Change a BSBW to a JSB.	
0000	84	:				
0000	85	:	V03-013	WHM0002	Bill Matthews	13-Dec-1983
0000	86	:			Fixed several calls to SGN\$GET_DEVICE to pass the unit number	
0000	87	:			to be connected not the maximum units.	
0000	88	:			Added support for the new CONNECT command qualifiers	
0000	89	:			/CSR_OFFSET and /VECTOR_OFFSET.	
0000	90	:				
0000	91	:	V03-012	JLV0312	Jake VanNoy	26-Oct-1983
0000	92	:			Fix bug for microVAX that allows nexus 0 in CONNECT.	
0000	93	:				
0000	94	:	V03-011	WHM0001	Bill Matthews	09-Dec-1983
0000	95	:			Changed some bsbw's to jsb's	
0000	96	:				
0000	97	:	V03-010	WMC0003	Wayne Cardoza	09-Aug-1983
0000	98	:			Fix loadable code error handling.	
0000	99	:			USEACTIVE should be in configutl.	
0000	100	:				
0000	101	:	V03-009	WMC0002	Wayne Cardoza	29-Jul-1983
0000	102	:			More features for code loading.	
0000	103	:				
0000	104	:	V03-008	WMC0001	Wayne Cardoza	27-Jul-1983
0000	105	:			Support general code loading.	
0000	106	:				
0000	107	:	V03-007	MSH0006	Maryann Hinden	24-Jun-1983
0000	108	:			Use \$BOOCMDDEF instead of \$BOODEF.	
0000	109	:				
0000	110	:	V03-006	MSH0005	Maryann Hinden	04-May-1983
0000	111	:			Changes to support CONFIGURE process.	
0000	112	:				
0000	113	:	V03-005	MSH0004	Maryann Hinden	13-May-1983
0000	114	:			Change some BSBW PUTERROR instructions to JSB instead.	



```

0000 115 :
0000 116 : V03-004 MSH0003 Maryann Hinden 31-Jan-1983
0000 117 : Add support for cluster device names.
0000 118 :
0000 119 : V03-003 TCM0001 Trudy C. Matthews 8-Nov-1982
0000 120 : Use new ADP$L_AVECTOR field in calculation of ACF$W_AVECTOR,
0000 121 : instead of calculating it from the adapter's TR number.
0000 122 :
0000 123 : V03-002 MSH0002 Maryann Hinden 22-Oct-1982
0000 124 : Fix broken BSBW.
0000 125 :
0000 126 : V03-001 MSH0001 Maryann Hinden 30-Sep-1982
0000 127 : Check for DDB$L_UCB = 0.
0000 128 : --
0000 129 :
0000 130 :
0000 131 : Include files:
0000 132 :
0000 133 : $ACFDEF : Define autoconfiguration block
0000 134 : $ADPDEF : Define adapter control block
0000 135 : $BOOCMDDEF : Define SYSGEN command options
0000 136 : $CLIDEF : Define CLI codes and values
0000 137 : $CRBDEF : Define CRB offsets
0000 138 : $DDBDEF : Define DDB offsets
0000 139 : $DYNDEF : Block types
0000 140 : $HLPDEF : Define HELP symbols
0000 141 : $IDBDEF : Define IDB offsets
0000 142 : $IHDEF : Image header offsets
0000 143 : $IPLDEF : Define IPLs
0000 144 : $JPIDEF : $GETJPI definitions
0000 145 : $LBRDEF : Librarian symbols
0000 146 : $OPCDEF : Operator message definitions
0000 147 : $PRDEF : Define processor registers
0000 148 : $PRMDEF : Parameter descriptor definitions
0000 149 : $SBDEF : SCS system block definitions
0000 150 : $SHRDEF : Error codes
0000 151 : $SLVDEF : Loadable code header
0000 152 : $SSDEF : Define system status values
0000 153 : $SYSGMSGDEF : Sysgen messages
0000 154 : $TPADEF : TPARSE definitions
0000 155 : $UCBDEF : Define UCB offsets
0000 156 : $VECDDEF : Define VEC offsets
0000 157 :
0000 158 :
0000 159 : Equated Symbols:
0000 160 :
0000000D 0000 161 : CR=13 : Character value for carriage return
0000000C 0000 162 : FF=12 : Character value for form feed
0000000A 0000 163 : LF=10 : Character value for line feed
00001000 0000 164 : UBA_IOBASE=8*512 : Offset from UBA configuration register
0000 165 : to base of I/O page
0000 166 :
0000 167 : Own Storage
0000 168 :
00000000 0000 169 : .PSECT $$$$000,NOEXE,NOWRT : PSECT to mark lower address
0000 170 : BOO$LOLIM:: : Marker definition
00000000 0000 171 : .PSECT ____ZZZ,WRT,PAGE : PSECT to mark upper address limit

```



0000	0000	172	BOOSHILIM::		
00000000	0000	173	.PSECT	NONPAGED_DATA	rd,wrt,noexe,quad
0000	0000	174			
00000200	0000	175	BOOSAB_PATCH::		: Non-paged Patch area
	0000	176	.BLKB	512	: One page
00002200	0200	177	BOOSAB_PRMBUF::		: Parameter buffer
	0200	178	.BLKB	512*16	: A generous buffer
00002400	2200	179	BOOSAB_LOADBUF::		: Buffer for code loader
	2200	180	.BLKB	512	
	2400	181	ACF\$GL_DDB::		
00000000	2400	182	.LONG	0	
	2404	183	ACF\$GL_UCB::		
00000000	2404	184	.long	0	
	2408	185	ACF\$GL_IDB::		
00000000	2408	186	.long	0	
	240C	187	ACF\$GL_CRB::		
00000000	240C	188	.long	0	
	2410	189	ACF\$GL_LASTDDB::		
00000000	2410	190	.long	0	
	2414	191	ACF\$GL_DPT::		
00000000	2414	192	.long	0	
	2418	193	ACF\$GL_SB::		
00000000	2418	194	.LONG	0	
	241C	195	BOO\$GL_COMBO_VECTOR_OFFSET::		: Offset to vector from start of combo
00000000	241C	196	.LONG	0	: device's vectors
	2420	197	BOO\$GL_COMBO_CSR_OFFSET::		: Offset to CSR from start of combo
00000000	2420	198	.LONG	0	: device's CSR
	2424	199	BOO\$GL_CONADP::		: Adapter TR number
FFFFFFFFE	2424	200	.LONG	-2	: Null value
	2428	201	BOO\$GL_CONCREG::		: Control register
FFFFFFFFF	2428	202	.LONG	-1	: Null value
	242C	203	BOO\$GL_CONCUNIT::		: Controller unit
FFFFFFFFF	242C	204	.LONG	-1	: Null value
	2430	205	BOO\$GL_CONNUMU::		: Number of Units to configure
00000001	2430	206	.LONG	1	: Default value is 1 unit
	2434	207	BOO\$GL_CONVECT::		: Vector offset
FFFFFFFFF	2434	208	.LONG	-1	: Null value
	2438	209	BOO\$GL_CONNUMV::		: Number of vectors
FFFFFFFFF	2438	210	.LONG	-1	: Null value
	243C	211	BOO\$GL_CONAUNIT::		: Adapter unit
FFFFFFFFF	243C	212	.LONG	-1	: Null value
	2440	213	BOO\$GL_CONDEV::		: Device name string address
FFFFFFFFF	2440	214	.LONG	-1	: Null value
	2444	215	BOO\$GL_CONDRV::		: Driver name string address
FFFFFFFFF	2444	216	.LONG	-1	: Null value
	2448	217	BOO\$GL_CONUNITS::		: Maximum units
00000000	2448	218	.LONG	0	
	244C	219	BOO\$GL_CONSYSID::		: System ID
00000000	244C	220	.LONG	0	: quadword
00000000	2450	221	.LONG	0	
	2454	222	BOO\$GL_CONCRB::		: CRB address
00000000	2454	223	.LONG	0	
	2458	224	BOO\$GL_CONFLAGS::		: Flags
00000000	2458	225	.LONG	0	
	245C	226	BOO\$GL_NEXTSTR::		: Next string location
00000000	245C	227	.LONG	0	
	2460	228	BOO\$GL_SELECT::		: Address of select list



00000000	2460	229	.LONG 0	:	
	2464	230	BOOSAL_CLIBLK::	:	CLI call back block
	2464	231	SCLIREQDESC	:	Get command call back block
	2464	232	RQTYPE=CLISK_GETCMD	:	
0000246C	2480	233	BOOSGQ_CMDESC==BOOSAL_CLIBLK*CLISW_RQSIZE	:	; Command descriptor address
	2480	234	BOOSGT_PROMPT::	:	Prompt string
00 20 20 3E 4E 45 47 53 59 53 0A 0D	2480	235	.ASCIZ <CR><LF>%SYSGEN> %	:	
	248C	236	BOOSAL_ACF::	:	Auto-configuration block
000024B4	248C	237	.BLKB ACFSC_LENGTH	:	Allocate space for it
	24B4	238	BOOSGQ_LIMITS::	:	High and low address limits for lockdown
00000000	24B4	239	.LONG BOOSLOLIM	:	Lower address bound
FFFFFFFF	24B8	240	.LONG BOOSHILIM-1	:	
	24BC	241	BOOSGQ_RETADR::	:	Return address receiver
00000000 00000000	24BC	242	.LONG 0,0	:	
	24C4	243	BOOSGL_RETSAVE::	:	Saved co-routine return address
00000000	24C4	244	.LONG 0	:	
	24C8	245	FACNAMED::	:	Facility name descriptor
000024D0 00000006	24C8	246	.LONG FACNAMSZ,FACNAME	:	
4E 45 47 53 59 53	24D0	247	FACNAME:.ASCII /SYSGEN/	:	
00000006	24D6	248	FACNAMSZ=.FACNAME	:	Length of facility name
	24D6	249	CONSNAME:	:	Console block storage
41 53 43 00	24D6	250	.ASCIC /CSA/	:	device name
03	24D6			:	
	24DA	251	BOOSGT_OPNAME::	:	Console terminal device name
41 50 4F 00	24DA	252	.ASCIC /OPA/	:	
03	24DA			:	
	24DE	253	BOOSGT_CVNAME::	:	Name of RL02 driver
52 45 56 49 52 44 56 43 00	24DE	254	.ASCIC /CVDRIVER/	:	
08	24DE			:	
	24E7	255	BOOSGT_DXNAME::	:	Name of floppy driver
52 45 56 49 52 44 58 44 00	24E7	256	.ASCIC /DXDRIVER/	:	
08	24E7			:	
	24F0	257	BOOSGT_DDNAME::	:	Name of TU58 driver
52 45 56 49 52 44 44 44 00	24F0	258	.ASCIC /DDDRIVER/	:	
08	24F0			:	
	24F9	259		:	
	24F9	260	BOOSGL_FILEADDR::	:	File spec address
00000000	24F9	261	.LONG 0	:	
	24FD	262	BOOSGB_FILELEN::	:	File spec length
00	24FD	263	.BYTE 0	:	
	24FE	264		:	
00000000	24FE	265	BOOSGL_PARINUSE::	:	
74 6E 65 72 72 75 43 00	2502	266	BOOSGT_CURRENT::	:	.LONG 0
07	2502			:	.ASCIC /Current/
65 76 69 74 63 41 00	250A	267	BOOSGT_ACTIVE::	:	.ASCIC /Active/
06	250A			:	
74 6C 75 61 66 65 44 00	2511	268	BOOSGT_DEFAULT::	:	.ASCIC /Default/
07	2511			:	
00002559	2519	269	BOOSGT_FILE::	:	.BLKB 64
	2559	270		:	
	2559	271	HELP_FILE:	:	Help library file name
45 48 24 53 59 53 00002561 010E0000	2559	272	.ASCID /SYSS\$HELP:SYSGEN.HLB/	:	
4C 48 2E 4E 45 47 53 59 53 3A 50 4C	2567			:	
42	2573			:	
00000001	2574	273	HELP_FLAG:	:	.long hlp\$m_prompt
00002580 010E0000	2578	274	HELP_DESC:	:	.ascid //
	2580	275		:	Filled in as pointer



```

00000000 2580 276 VALID_PAR_FILE: ; Valid parameter file flag
00000000 2580 277 .LONG 0
00000000 2584 278 SAVE_DOT: ; Save dot through USE filespec
00000000 2584 279 .LONG 0
00000000 2588 280 FULL_NAME_PTR: ; Full device name
00000000 2588 281 .LONG 0
258C 282 ; MSCP initialization routine default argument list
258C 283
258C 284 MSCP_ARG_LIST:
00000008 258C 285 .LONG 8 ; Number of arguments
00000001 2590 286 .LONG 1 ; Function code(load and start server)
00008000 2594 287 .LONG 32768 ; Default buffer size
00000004 2598 288 .LONG 4 ; Default number of receive credits for each host
0000000F 259C 289 .LONG 15 ; Default number of hosts supported
00000014 25A0 290 .LONG 20 ; Default time out
00000004 25A4 291 .LONG 4 ; Default priority
00001000 25A8 292 .LONG 4096 ; Default for minimum qualifier
00004000 25AC 293 .LONG 16384 ; Default for maximum qualifier
000025BC 25B0 294 .BLKL 3 ; Space for new args
00000030 25BC 295 MSCP_ARG_LIST_SIZE = -MSCP_ARG_LIST
25BC 296
25BC 297 BOO$GL_LOAD_ARGS: ; Argument list block loadable code init
000025EC 25BC 298 .BLRB MSCP_ARG_LIST_SIZE ; routine
25EC 299
25EC 300
25EC 301
50 43 53 4D 00' 25EC 302 MSCP_NAME: .ASCIC /MSCP/ ;MSCP server name
04 25EC
25F1 303
25F1 304 ; AUTO ALL /LOG storage
25F1 305
25F1 306 CTRSTR_AUTOLOG: .ascid / !AC!UW/
25FF
55 21 43 41 21 20 000025F9'010E0000' 2600 307 CTRSTR_AUTOLOG_UNIT: .ascid /,!UW/
57 55 21 2C 00002608'010E0000' 260C 308 Outlen_unit: .long 0
00000000 2610 309 Outlen: .long 0
00002628 2614 310 Boo$gt_save_devname: .blkb 20
00002630'010E0000' 2628 311 outbuf: .ascid //
00002694 2630 312 outbuf_str: .blkb 100
2694 313
2694 314 ; Send operator message data
2694 315
2694 316 OPERGETJPI: ; $GETJPI item list
0004 2694 317 .WORD 4 ; Buffer length
0319 2696 318 .WORD JPI$ PID ; Process ID code
000026B0' 2698 319 .ADDRESS OPERMSGPID ; Buffer address
00000000 269C 320 .LONG 0 ; Don't return length
00000000 26A0 321 .LONG 0 ; List terminator
26A4 322
26A4 323 OPERMSGVEC: ; $PUTMSG message vector
0003 26A4 324 .WORD 3 ; Argument count
000F 26A6 325 .WORD ^B1111 ; Default message flags
26A8 326 OPERMSGID: ; Message ID
00000000 26A8 327 .LONG 0
26AC 328 OPERMSGFAO: ; FAO argument count
0001 26AC 329 .WORD 1
0000 26AE 330 .WORD 0 ; No new message flags

```

00000000	26B0	331	OPERMSGPID:			; PID of this process
	26B0	332	.LONG	0		
000026B8	26B4	333	OPERMSGNAM:			; File specification
	26B4	334	.ADDRESS		OPERNAMDESC	
	26B8	335				
00000000 00000000	26B8	336	OPERNAMDESC:			
	26B8	337	.LONG	0,0		
	26C0	338				
00000000	26C0	339	OPERMSG:			; Message descriptor
000026C8	26C0	340	.LONG	0		
	26C4	341	.ADDRESS		OPERMSGBUF	
	26C8	342				
00000103	26C8	343	OPERMSGBUF:			; Message buffer
00000000	26C8	344	.LONG	OPC\$_RQ_RQST!<OPC\$_NM_CENTRL@8>		; Message type and target
	26CC	345	.LONG	0		; No reply message
000027D0	26D0	346	OPERMSGTXT:			; Message text
	26D0	347	.BLKB	256		
	27D0	348				
	27D0	349	.IF	NDF,CONFIGSW		; SYSGEN-specific code



```

27D0 351 .SBTTL BOO$USEFILE - Use parameter file
27D0 352 :++
27D0 353 : Functional description:
27D0 354 : BOO$USEFILE reads the specified file in response to the USE
27D0 355 : command and merges all of the values specified in that file into
27D0 356 : the working copy of the parameter values. This is accomplished
27D0 357 : by looking up each value specified and merging the associated
27D0 358 : value.
27D0 359 :
27D0 360 : Calling sequence:
27D0 361 : CALLG arglist,BOO$USEFILE
27D0 362 :
27D0 363 : Input Parameters:
27D0 364 : TPASL_TOKENCNT(AP) - Length of file name string
27D0 365 : TPASL_TOKENPTR(AP) - Address fo file name string
27D0 366 : Output Parameters:
27D0 367 : R0 - Completion status code
27D0 368 :
27D0 369 :--
27D0 370
00000000 371 .PSECT PAGED_CODE rd,nowrt,exe,long
0000 372
03FC 0000 373 .Entry BOO$USEFILE, ^M<R2,R3,R4,R5,R6,R7,R8,R9> ; Entry mask
0002 374
0002 375
00000000'8F E2 0002 376 BBSS #EXESV WRITESYSPARAMS,- : Use a file => write current needed
00 00000000'GF 0008 377 G^EXESGL_DYNAMIC_FLAGS,1$;
00002584'EF 00000000'EF D0 000E 378 1$:
57 10 AC 9E 0019 379 MOVL BOO$GL_DOT,L^SAVE_DOT : Save dot
FFEO' 30 001D 380 MOVAB TPASL_TOKENCNT(AP),R7 : Set address of file name descriptor
04 50 E8 0020 381 BSBW BOO$FIOPEN : Open specified file
50 01 3C 0023 382 BLBS R0,20$ : Continue if success
04 0026 383 10$: MOVZWL #1,R0 : Force success
56 00000200'EF 9E 0027 384 RET
59 10 D0 002E 385 20$: MOVAB BOO$AB_PRMBUF,R6 : Set address of parameter buffer
FFCC' 30 0031 386 MOVL #16,R9 : Set size of buffer
EC 50 E9 0034 387 BSBW BOO$READFILE : Read file content into parameter buffer
58 00000200'EF 9E 0037 388 BLBC R0,10$ : Exit if error
00000000'EF 68 20 28 003E 389 MOVAB BOO$AB_PRMBUF,R8 : Init pointer to parameter buffer
58 20 C0 0046 390 MOVCL #32,(R8),EXESGT_STARTUP : Set startup command file name
00002580'EF D4 0049 391 ADDL #32,R8 : and advance buffer pointer
68 D5 004F 392 CLRL VALID_PAR_FILE : Initialize valid parameter file flag
56 13 0051 393 30$: TSTL (R8) : Check for end of list
10 AC 68 9A 0053 394 BEQL DONE : Branch if yes
14 AC 01 A8 9E 0057 395 MOVZBL (R8),TPASL_TOKENCNT(AP) : Set token count for search
58 10 C0 005C 396 MOVAB 1(R8),TPASL_TOKENPTR(AP) : And address of string
1C AC 88 D0 005F 397 ADDL #16,R8 : Advance to value
00000000'EF 6C FA 0063 398 MOVL (R8)+,TPASL_NUMBER(AP) : Set number
E2 50 E9 006A 399 CALLG (AP),L^BOO$SEARCH : Search for parameter
00002580'EF 01 D0 006D 400 BLBC R0,30$ : Next parameter if not found
54 20 AC D0 0074 401 MOVL #1,VALID_PAR_FILE : Indicate valid parameter file
22 10 A4 10 E1 0078 402 MOVL TPASL_PARAM(AP),R4 : Get a pointer to the parameter descriptor
14 AC 78 DE 007D 403 BBC #PRMSV_ASCII,PRMSL_FLAGS(R4),40$ : Branch if not an ascii parameter
50 14 A4 9A 0081 404 MOVAL -(R8),TPASL_TOKENPTR(AP) : Get a pointer to the parameter value
50 50 FD 8F 78 0085 405 MOVZBL PRMSB_SIZE(R4),R0 : Get parameter size in bits
10 AC 50 9A 008A 406 ASHL #-3,R0,R0 : Set parameter size
407 MOVZBL R0,TPASL_TOKENCNT(AP)

```

```

50 03 C0 008E 408 ADDL2 #3,R0 ; Round size up to the next longword
50 03 CA 0091 409 BICL2 #3,R0 ;
58 50 C0 0094 410 ADDL2 R0,R8 ; Advance past value
0000'CF 6C FA 0097 411 CALLG (AP),W^BOO$SETASCII ; Set the value of the parameter
00000000'EF FF80 31 009C 412 BRW 30$ ; Continue with the next parameter
FFA6 6C FA 009F 413 40$: CALLG (AP),L^BOO$SETVALUE ; Set value of parameter
FF54 31 00A6 414 BRW 30$ ; Continue with next parameter
09 00002580'EF FF54 30 00A9 415 DONE: BSBW BOO$FILCLOSE ; Close the file
50 007C80EA 8F E8 00AC 416 BLBS VALID PAR FILE,10$ ; If LBS, valid parameter file
21 11 D0 00B3 417 MOVL #SYS$$_NOTPARAM,R0 ; Set error
00BA 418 BRB 20$ ; Branch
00BC 419 10$:
00BC 420 ;
00BC 421 ; Set file name in BOO$GL_PARINUSE
00BC 422 ;
58 00002519'EF DE 00BC 423 MOVAL BOO$GT_FILE,R8 ; Set address of String
000024FE'EF 58 D0 00C3 424 MOVL R8,BOO$GL_PARINUSE ; Set address
68 000024FD'EF 9A 00CA 425 MOVZBL BOO$GB_FILELEN,(R8) ; Set count
000024F9'FF 68 28 00D1 426 MOVCL (R8),@BOO$GL_FILEADDR,-
01 A8 00D8 427 1(R8) ; Move string
00DA 428
00DA 429 MOVZWL #SS$ NORMAL,R0 ; Return success
00000000'EF 50 01 3C 00DA 429 MOVZWL #SS$ NORMAL,R0 ; Return success
00002584'EF D0 00DD 430 20$: MOVL L^SAVE_DOT,BOO$GL_DOT ; Restore dot
04 00E8 431 RET ;
00E9 432 .ENDC ; End of SYSGEN-specific code

```



```

00E9 434 .SBTTL BOO$USEACT - Use active parameters
00E9 435 :++
00E9 436 : Functional description:
00E9 437 : This routine copies the parameter values from the running
00E9 438 : system to the working copy of the parameter values.
00E9 439 : Calling sequence:
00E9 440 :
00E9 441 : CALLS #0,BOO$USEACT
00E9 442 :
00E9 443 : Input parameters:
00E9 444 : None
00E9 445 : Output Parameters:
00E9 446 : R0 - Completion status code
00E9 447 :--
003C 00E9 448 .Entry BOO$USEACT,^M<R2,R3,R4,R5>
00E8 450
00E8 451 MOV C3 #EXESC_SYSPARSZ,- ; Move parameters
00EF 452 MMGSA_SYSPARAM,EXESA_SYSPARAM
00F9 453 MOVAL BOO$GT_ACTIVE,-
00FF 454 BOO$GL_PARINUSE ; Set parameter in use
0104 455 MOVL #1,R0 ; Return success
0107 456 RET
0108 457 .IF NDF,CONFIGSW ; SYSGEN-specific code

```

```

0108 459 .SBTTL BOO$WRTACT - Write parameters to system
0108 460 :++
0108 461 : Functional Description:
0108 462 : This routine writes the parameters in the working parameter
0108 463 : buffer to the system's parameter area. Only dynamic
0108 464 : parameters are copied.
0108 465 :
0108 466 : Calling Sequence:
0108 467 : CALLS #0,BOO$WRTACT
0108 468 :
0108 469 : Input Parameters:
0108 470 : None
0108 471 :
0108 472 : Output Parameters:
0108 473 : R0 - Completion status code
0108 474 :--
0108 475
00000000 476 .PSECT NONPAGED_CODE rd,nowrt,exe,long
0000 477
0000 478 .Entry BOO$WRTACT, ^M<>
0002 479
0002 480 $CMKRNLS B^10$,(AP) ; Do it in kernel mode
0000140'EF E9 000E 481 BLBC R0,1$ ; If LBC, error
007CA013 16 0011 482 JSB BOO$SENDOPER ; Notify operator of WRITE ACTIVE
09 50 E8 001B 483 .LONG SYSG$_WRITEACT
00000000'EF 16 001E 484 BLBS R0,5$ ; If LBS, success
50 01 D0 0024 485 1$: JSB PUTERROR ; Report error
04 0027 486 MOVL #1,R0 ; Force success
0028 487 5$: RET
0028 488
55 00000000'EF 003C 0028 489 10$: .WORD ^M<R2,R3,R4,R5>
9E 002A 490 MOVAB L^BOO$A PRMBLK,R5 ; Get base of parameter blocks
0031 491 DSBINT #IPL$_SCHED ; Raise IPL to prevent being unscheduled
0037 492 ; (Assumes pages are locked in W.S.)
0037 493
0037 494 ASSUME PRMSL_ADDR EQ 0
0037 495
53 65 D0 0037 496 20$: MOVL PRMSL_ADDR(R5),R3 ; Get address of parameter
28 13 003A 497 BEQL 40$ ; Reached the end
00 E1 003C 498 BBC #PRMSV DYNAMIC,- ; Branch if this is not a
1E 10 A5 003E 499 PRMSL_FLAGS(R5),30$ ; dynamic parameter
51 15 A5 9A 0041 500 MOVZBL PRMSB_POS(R5),R1 ; Get position of parameter
63 14 A5 51 EF 0045 501 EXTZV R1,PRMSB_SIZE(R5),(R3),R2 ; Extract parameter value
50 00000000'EF 9E 004B 502 MOVAB L^EXESA_SYSPARAM,R0 ; Get address of working buffer
53 50 C2 0052 503 SUBL R0,R3 ; Get parameter offset
14 A5 51 52 F0 0055 504 INSV R2,R1,PRMSB_SIZE(R5),- ; Store in system
00000000'E3 005A 505 L^MMGSA_SYSPARAM(R3)
005F 506
55 32 C0 005F 507 30$: ADDL #PRMSC_LENGTH,R5 ; Point to next paramter block
D3 11 0062 508 BRB 20$ ; Repeat
0064 509
0064 510 ; Copy dynamic flags from default flags to R0
0064 511
50 FFFFFFFF'BF CB 0064 512 40$: BICL3 #^C<PRMSM_DYNFLAGS>,-
00000000'EF 006A 513 MMGSA_SYSPARAM+<EXESGL_DEFFLAGS-EXESA_SYSPARAM>,R0
00000000'BF CA 0070 514 BICL #PRMSM_DYNFLAGS,- ; Clear dynamic flags in real flags
00000000'EF 0076 515 EXESGL_FLAGS

```



SYSGEN  
V04-002

J 6  
- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00  
BOO\$WRTACT - Write parameters to system 14-SEP-1984 16:09:11 [BOOTS.SRC]SYSGEN.MAR;3

Page 12  
(2)

00000000'EF	50	C8	0078	516	BISL	R0,EXE\$GL_FLAGS	; Set dynamic flags in real flags
			0082	517			
			0082	518	ENBINT		; Lower IPL
50	01	D0	0085	519	MOVL	#1,R0	; Set success
		04	0088	520	RET		

```

0089 522 .SBTTL BOO$WRTCUR - Write Current Parameters
0089 523 :++
0089 524 : Functional Description:
0089 525 : This routine writes the parameters from the working parameter
0089 526 : buffer to the system parameter file on disk. They will take effect the
0089 527 : next time the system is booted.
0089 528 :
0089 529 : Calling Sequence:
0089 530 : CALLS #0,BOO$WRTCUR
0089 531 :
0089 532 : Input parameters:
0089 533 : None
0089 534 :
0089 535 : Output Parameters:
0089 536 : R0 - Completion status code
0089 537 :--
0089 538 :
00000108 539 .PSECT PAGED_CODE rd,nowrt,exe,long
0108 540
03FC 0108 541 .Entry BOO$WRTCUR, ^M<R2,R3,R4,R5,R6,R7,R8,R9>
010A 542
00000000'8F E5 010A 543 BBCC #EXESV WRITESYSPARAMS,- : Don't do WRITE CURRENT again in startup
00 00000000'GF 0110 544 G^EXESGL DYNAMIC_FLAGS,10$:
50 00000000'EF 9E 0116 545 10$: MOVAB BOO$GT SYSPARNAME,R0 : Get address of system .PAR file name
10 AC 80 9A 011D 546 MOVZBL (R0)+,TPASL TOKENCNT(AP): Set up for call to BOO$WRTSYSPARFILE
14 AC 50 D0 0121 547 MOVL R0,TPASL TOENPTR(AP)
00000000'GF 6C FA 0125 548 CALLG (AP),G^BOO$WRTSYSPARFILE: Call the routine to write out the file
0A 50 E9 012C 549 BLBC R0,20$ : Branch if error
000E 30 012F 550 BSBW BOO$SENDOPER : Notify operator of WRITE CURRENT
007CA01B 0132 551 .LONG SYSG$_WRITECUR
03 50 E8 0136 552 BLBS R0,30$ : If LBS, success
FEC4' 30 0139 553 20$: BSBW PUTERROR : Report error
50 01 D0 013C 554 30$: MOVL #1,R0 : Return success
04 013F 555 RET
0140 556

```



```
0140 558 .SBTTL BOO$SENDOPER - Output facility error message to operator
0140 559 :
0140 560 : Functional Description:
0140 561 : BOO$SENDOPER outputs an error message to the operator.
0140 562 :
0140 563 : Calling Sequence:
0140 564 : BSBW BOO$SENDOPER
0140 565 : .LONG <msg-id>
0140 566 :
0140 567 BOO$SENDOPER::
000026A8'EF 00 BE D0 0140 568 MOVL @ (SP), OPERMSGID ; Put message ID in vector
6E 04 C0 0148 569 ADDL2 #4, (SP) ; Advance return address
7B 50 E9 014B 570 $GETJPI S ITMLST=OPERGETJPI ; Get process ID
000026A4'EF 03 D0 0165 571 BLBC R0, 10$ ; If LBC, error
000026AC'EF 01 D0 016C 572 MOVL #3, OPERMSGVEC ; Assume WRITE ACTIVE
000026B4'EF D4 0173 573 MOVL #1, OPERMSGFAO
000026A8'EF 007CA01B 8F D1 0179 574 CLRL OPERMSGNAM
2D 12 0184 575 CMPL #SYSG$_WRITECUR, OPERMSGID ; WRITE CURRENT ?
000026A4'EF D6 0186 576 BNEQ S$ ; If NEQ, no
000026AC'EF D6 018C 577 INCL OPERMSGVEC ; Set up WRITE CURRENT
000026B8'EF 000026B8'EF 9E 0192 578 INCL OPERMSGFAO
000026B8'EF 00000000'EF 9A 019D 579 MOVAB OPERNAMDESC, OPERMSGNAM
000026BC'EF 00000000'EF D0 01A8 580 MOVZBL RIO_INPNAM+NAM$B_RSL, OPERNAMDESC; Build descriptor
01B3 581 MOVL RIO_INPNAM+NAM$B_RSA, OPERNAMDESC+4
01B3 582 5$: $PUTMSG_S - ; Get and format message
01B3 583 MSGVEC=OPERMSGVEC, -
01B3 584 ACTRTN=666$
13 50 E9 01CA 585 BLBC R0, 10$ ; If LBC, error
06 50 E8 01CD 586 $SENDOPR S MSGBUF=OPERMSG
FE1D' 30 01E0 587 BLBS R0, 20$ ; If LBS, success
50 01  D0 01E3 588 10$: BSBW PUTERROR ; Report error
01E6 589 20$: MOVL #1, R0 ; Force success
05 01E6 590 RSB
01E7 591 666$: .WORD *M<R2,R3,R4,R5>
003C 01E7 592 .WORD @4(AP), R0 ; Get string descriptor
50 04 BC 7D 01E9 593 MOVQ @4(AP), R0 ; Store total operator message size
000026C0'EF 50 08 C1 01ED 594 ADDL3 #OPC$L MS TEXT, R0, OPERMSG; Copy text to operator message buffer
000026D0'EF 61 50 28 01F5 595 MOVC3 R0, (R1), OPERMSGTXT ; Prevent message output to SYS$OUTPUT
D4 01FD 596 CLRL R0
04 01FF 597 RET
0200 598
0200 600 .ENDC ; End of SYSGEN-specific code
```



```

0200 602 .SBTTL BOO$CONFIGALL - Auto-configure all adapters
0200 603 :++
0200 604 : Functional Description:
0200 605 : BOO$CONFIGALL is called to implement the 'AUTOCONFIGURE ALL'
0200 606 : command. All standard devices supported by VAX/VMS will be
0200 607 : located and connected for use with any necessary drivers being
0200 608 : loaded.
0200 609 :
0200 610 : Calling Sequence:
0200 611 : CALLG ARLIST,BOO$CONFIGALL
0200 612 :
0200 613 : Output parameters:
0200 614 : R0 - Completion status code
0200 615 : --
0200 616 :
00000089 617 .PSECT NONPAGED_CODE rd,nowrt,exe,long
0089 618 :
OFFC 0089 619 .Entry BOO$CONFIGALL, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; Entry mask
008B 620 :
08 00000000'EF 00000000'8F E1 008B 621 BBC #EXESV_NOAUTOCNF,EXESGL_DEFFLAGS,5$; do we allow auto configure
50 007C8002 8F D0 0097 622 MOVL #SYSGS_NOAUTOCNF,R0 ; Give them a no autoconfigure error
04 009E 623 RET ; and return
009F 624 :
FF5E' 30 009F 625 5$: BSBW BOO$LOCK_GEN ; Lock SYSGEN database
07 50 E8 00A2 626 BLBS R0,7$ ; If no error, continue
00000000'EF 16 00A5 627 JSB PUTERROR
04 00AB 628 RET
00AC 629 :
FF51' 30 00AC 630 7$: BSBW IOC$AUTORESET ; Reset controller characters for device
00AF 631 : names
5B D4 00AF 632 CLRL R11 ; Indicate no ADP address yet
5B DD 00B1 633 10$: PUSHL R11 ; Set as argument
0000013B'EF 01 FB 00B3 634 CALLS #1,NEXTADP ; Get next ADP address
29 50 E9 00BA 635 BLBC R0,CONFIG_EXIT ; Branch if error (NOPRIV)
5B 51 D0 00BD 636 MOVL R1,R11 ; Check return status
10 18 00C0 637 BGEQ 20$ ; Branch if done
5B DD 00C2 638 PUSHL R11 ; Set as ADP argument
018C'CF 01 FB 00C4 639 CALLS #1,W^CONFIGADP ; Configure the entire adapter
E5 50 E8 00C9 640 BLBS R0,10$ ; Continue if no error
00000000'EF 16 00CC 641 JSB PUTERROR ; Report error
50 01 D0 00D2 642 20$: MOVL #1,R0 ; Set success
00D5 643 :
09 00000000'EF 0C E1 00D5 644 BBC #BOOCMD$V AUTOLOG,L^BOO$GL_CMDOPT,CONFIG_EXIT ; Branch if not /LOG
00002614'EF D4 00DD 645 CLRL BOO$GT_SAVE_DEVNAME ; Clear name
01A9 30 00E3 646 BSBW AUTOLOG ; Output last line if there is one
00E6 647 :
00E6 648 CONFIG_EXIT:
50 DD 00E6 649 PUSHL R0 ; Save status
FF15' 30 00E8 650 BSBW BOO$UNLOCK_GEN ; Unlock SYSGEN database
06 50 E8 00EB 651 BLBS R0,35$ ; If no error, continue
00000000'EF 16 00EE 652 JSB PUTERROR ; Give error message
50 8ED0 00F4 653 35$: POPL R0 ; Restore status
04 00F7 654 RET ;
00F8 655 :
OFFC 00F8 656 .Entry BOO$CONFIGONE, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; Entry mask
00FA 657 :
FF03' 30 00FA 658 BSBW BOO$LOCK_GEN ; Lock SYSGEN database

```



```

07 50 E8 00FD 659 BLBS R0,5$ ; If no error, continue
00000000'EF 16 0100 660 JSB PUTERROR ; Give error message
04 0106 661 RET ;
FEF6' 30 0107 663 5$: BSBW IOC$AUTORESET ; Reset controller characters for device
010A 664 ; device names
1C AC DD 010A 665 PUSHL TPASL_NUMBER(AP) ; Set TR number of adapter
63'AF 01 FB 010D 666 CALLS #1,B^LOCADP ; Locate adapter control block
D2 50 E9 0111 667 BLBC R0,CONFIG_EXIT ; Branch if error (NOPRIV)
51 DD 0114 668 PUSHL R1 ; Set as argument to CONFIGADP
0D 13 0116 669 BEQL 10$ ; Done if no adapter
8C'AF 01 FB 0118 670 CALLS #1,B^CONFIGADP ; Configure adapter
06 50 E8 011C 671 BLBS R0,10$ ; Continue if no error
00000000'EF 16 011F 672 JSB PUTERROR ; Give error status
50 01 D0 0125 673 10$: MOVL #1,R0 ; Set success for parse
B6 00000000'EF 0C E1 0128 674 BBC #BOOCMD$V AUTOLOG,L^BOOS$GL CMOPT,CONFIG_EXIT ; Branch if not /LOG
00002614'EF D4 0130 675 CLRL BOOS$GT_SAVE_DEVNAME ; Clear name
0156 30 0136 676 BSBW AUTOLOG ; Output last line if there is one
AB 11 0139 677 20$: BRB CONFIG_EXIT ;
013B 678 ;
013B 679 NEXTADP: ; Return next ADP address in R0
0000 013B 680 .WORD 0 ; Null entry mask
013D 681 $CMEXEC_S B^10$,(AP) ; Call real routine in exec mode
04 0149 682 RET ;
014A 683 ;
0000 014A 684 10$: .WORD 0 ; Null entry mask
51 04 AC D0 014C 685 MOVL 4(AP),R1 ; Get current address
06 13 0150 686 BEQL 20$ ; 0 => start of list
51 04 A1 D0 0152 687 MOVL ADPSL_LINK(R1),R1 ; Flink onward
07 11 0156 688 BRB 30$ ;
51 00000000'EF D0 0158 689 20$: MOVL IOC$GL_ADPLIST,R1 ; Return head of list
50 01 D0 015F 690 30$: MOVL #1,R0 ;
04 0162 691 RET ;
0163 692 ;
0163 693 LOCADP: ; Return address of ADP for TR number
0000 0163 694 .WORD 0 ;
0165 695 $CMEXEC_S B^5$,(AP) ; Call routine in exec mode
04 0171 696 RET ;
0172 697 ;
0000 0172 698 5$: .WORD 0 ; Null entry mask
51 FFFFFFFC'EF 9E 0174 699 MOVAB IOC$GL_ADPLIST-ADPSL_LINK,R1 ; Set starting address
51 04 A1 D0 017B 700 10$: MOVL ADPSL_LINK(R1),R1 ; Flink onward
07 13 017F 701 BEQL 20$ ; Done if at end
0C A1 04 AC B1 0181 702 CMPW 4(AP),ADPSW_TR(R1) ; Is this the specified TR?
F3 12 0186 703 BNEQ 10$ ; No, try another
50 01 D0 0188 704 20$: MOVL #1,R0 ;
04 018B 705 RET ;
018C 706 ;
00FC 018C 707 .Entry CONFIGADP, ^M<R2,R3,R4,R5,R6,R7>; Entry mask
018E 708 ;
000024C4'EF D4 018E 709 CLRL BOOS$GL RETSAVE ; Zap return address for initial call
10 00000000'EF 06 E1 0194 710 BBC #BOOCMD$V_SELECT,L^BOOS$GL CMOPT,10$ ; Mutually exclusive - test
08 00000000'EF 07 E1 019C 711 BBC #BOOCMD$V_EXCLUDE,L^BOOS$GL CMOPT,10$ ; to make sure one bit clear
50 007C808A 8F D0 01A4 712 MOVL #SYS$G$_CONFQUAL,R0 ; Conflicting qualifiers
04 01AB 713 RET ;
01AC 714 ;
01FA'CF 6C FA 01AC 715 10$: CALLG (AP),W^50$ ; Call configure one device

```



```

09 50 E8 01B1 716 BLBS R0,20$ ; Branch if not done with this adapter
50 24 B1 01B4 717 CMPW #$$$_NOPRIV,R0 ; Was there a privilege error
03 13 01B7 718 BEQL 15$ ; Yes, branch
50 01 D0 01B9 719 MOVL #1,R0 ; Set success
04 01BC 720 15$: RET ; and return
01BD 721
55 0000248C'EF 9E 01BD 722 20$: MOVAB BOOS$AL_ACF,R5 ; Set address of arguments describing device
01C4 723
1C A5 B4 01C4 724 CLRW ACF$W_MAXUNITS(R5) ; Always use driver specified max units
56 00002460'EF D0 01C7 725 MOVL L^BOOS$GL_SELECT,R6 ; Get pointer to select list
06 13 01CE 726 BEQL 35$ ; Branch if null
00B7 30 01D0 727 BSBW SELECT ; Check select/exclude string
D6 50 E9 01D3 728 BLBC R0,10$ ; Branch if device is not to be configured
01D6 729
11 0B A5 03 E0 01D6 730 35$: BBS #ACF$V_NOLOAD_DB,ACF$B_AFLAG(R5),38$ ; Branch if not loading databases
09 00000000'EF 0C E1 01DB 731 BBC #BOOS$V_AUTOLOG,L^BOOS$GL_CMDOPT,38$ ; Branch if not logging
00A9 30 01E3 732 BSBW AUTOLOG ; Branch to output log
03 50 E8 01E6 733 BLBS R0,38$ ; Branch if no error
FE14' 30 01E9 734 BSBW PUTERROR ; Give error message
01EC 735
0000'CF 65 FA 01EC 736 38$: CALLG (R5),W^IOGEN$LOADER ; Load database and driver if necessary
B8 50 E8 01F1 737 BLBS R0,10$ ; Branch if no error
FE09' 30 01F4 738 BSBW PUTERROR ; Give error message
FFB2 31 01F7 739 BRW 10$ ; continue loop
01FA 740
0000 01FA 741 50$: .WORD 0
01FC 742 $CMKRNLS B^55$,(AP) ; Call auto configure in kernel mode
04 0208 743 RET
0209 744
OFFC 0209 745 55$: .WORD ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ;
D0 020B 746 MOVL BOOS$GL_RETSAVE,R0 ; Get saved return address
07 12 0212 747 BNEQ 60$ ; Branch if one present
50 00000000'EF 9E 0214 748 MOVAB IOC$AUTOCONFIG,R0 ; Else use main entry point
58 04 AC D0 021B 749 60$: PUSH R0 ; Stack call back address
56 68 D0 0221 751 MOVL ADP$L_CSR(R8),R6 ; Get address of ADP
57 0000248C'EF 9E 0224 752 MOVAB BOOS$AC_ACF,R7 ; Get Configuration register address
022B 753 SETIPL #31 ; Address of configuration control block
9E 16 022E 754 JSB @ (SP)+ ; Disable interrupts
0230 755 SETIPL #0 ; Call Auto configuration code
000024C4'EF 8E D0 0233 756 MOVL (SP)+,BOOS$GL_RETSAVE ; Enable interrupts
06 50 E8 023A 757 BLBS R0,70$ ; Save return
000024C4'EF D4 023D 758 CLRL BOOS$GL_RETSAVE ; Continue if another device
0243 759 ; Else clear return
0D 0B A7 03 E1 0243 760 70$: BBC #ACF$V_NOLOAD_DB,ACF$B_AFLAG(R7),80$ ; Branch if loading database
7E 12 A7 3C 0248 761 MOVZWL ACF$W_UNIT(R7),-(SP) ; Get unit number
14 A7 DD 024C 762 PUSHL ACF$L_DEVNAME(R7) ; Get device name
010B 30 024F 763 BSBW SGN$GET_DEVICE_LOCK_IODB ; Get device database
5E 08 C0 0252 764 ADDL2 #8,SP ; Clear stack
04 0255 765 80$: RET ; And return
50 01 3C 0256 766 90$: MOVZWL #1,R0 ; Set success status
04 0259 767 RET ; and return
025A 768
025A 769 ; SELECT - decide whether current device name is one of those either
025A 770 ; specified in /SELECT or /EXCLUDE
025A 771
025A 772 ; Returns: R0 = 1 ==> configure device

```



```

                                025A 773 ;          R0 = 0  ==> don't configure device
                                025A 774 ;
                                025A 775
57 14 A5 D0 025A 776 SELECT:
54 86 9A 025A 777 10$:  MOVL  ACF$DEVNAME(R5),R7      ; Get pointer to device name
10 13 025E 778      MOVZBL (R6)+,R4                    ; Get length of select entry
54 87 91 0261 779      BEQL  20$                        ; End of list, no match
06 19 0263 780      CMPB  (R7)+,R4                    ; Compare with device entry
67 66 54 29 0266 781      BLSS  15$                     ; Branch if select longer than device
13 13 0268 782      CMPC3  R4,(R6),(R7)                ; Do we have a match?
56 54 C0 026C 783      BEQL  40$                        ; Yes, check SELECT or EXCLUDE
E7 11 026E 784 15$:  ADDL  R4,R6                        ; Advance to next entry in select list
                                0271 785      BRB  10$    ; And try again
                                0273 786
03 00000000*EF 50 D4 0273 787 20$:  CLRL  R0              ; Assume don't configure
07 01 E1 0275 788      BBC   #BOOCMD$V_EXCLUDE,BOOS$GL_CMDOPT,30$ ; Branch if SELECT
50 01 D0 027D 789      MOVL  #1,R0                      ; EXCLUDE - configure device
                                0280 790 30$:  RSB
                                0281 791
03 00000000*EF 50 D4 0281 792 40$:  CLRL  R0              ; Assume don't configure
07 01 E0 0283 793      BBS   #BOOCMD$V_EXCLUDE,BOOS$GL_CMDOPT,50$ ; Branch if EXCLUDE
50 01 D0 028B 794      MOVL  #1,R0                      ; SELECT - configure device
                                028E 795 50$:  RSB

```



```

028F 797 .SBTTL AUTOLOG - AUTO ALL /LOG formatting
028F 798
028F 799 AUTOLOG::
55 0000248C'EF 9E 028F 800 MOVAB BOOSAL_ACF,R5 ; Address of configuration control block
56 14 A5 D0 0296 801 MOVL ACF$DEVNAME(R5),R6 ; Get address of current device
57 86 9A 029A 802 MOVZBL (R6)+,R7 ; Get count and addr.
00002614'EF 66 57 29 029D 803 CMPC3 R7,(R6),BOOSGT_SAVE_DEVNAME ; Compare to previous string
39 12 02A5 804 BNEQ 50$ ; Branch if new device
02A7 805
02A7 806 $FAO_S CTRSTR=CTRSTR_AUTOLOG_UNIT,- ; Format Unit Number
02A7 807 OUTBUF=OUTBUF,-
02A7 808 OUTLEN=OUTLEN_UNIT,-
02A7 809 P1=ACF$W_UNIT(R5)
03 50 E8 02C3 810 BLBS R0,40$ ; Branch if OK
0081 31 02C6 811 BRW 100$ ; Branch if error
02C9 812
2610'CF 260C'CF C0 02C9 813 40$: ADDL2 W^OUTLEN_UNIT,W^OUTLEN ; Add to total length
262C'CF 260C'CF C0 02D0 814 ADDL2 W^OUTLEN_UNIT,W^OUTBUF+4 ; Add to descriptor
2628'CF 260C'CF A2 02D7 815 SUBW2 W^OUTLEN_UNIT,W^OUTBUF ; Subtract from length
6A 11 02DE 816 BRB 100$ ; Return with success
02E0 817
2610'CF 05 02E0 818 50$: TSTL W^OUTLEN ; Is this a first call to this routine?
21 13 02E4 819 BEQL 70$ ; Branch if yes
02E6 820
262C'CF 2630'CF DE 02E6 821 MOVAL W^OUTBUF_STR,W^OUTBUF+4 ; reset descriptor
0000'CF 2610'CF B0 02ED 822 MOVW W^OUTLEN,W^RIOSGW_OUTLEN ; Length of string
0000'CF 28 02F4 823 MOVW W^RIOSGW_OUTLEN,-
2630'CF 02F8 824 W^OUTBUF_STR,-
0000'CF 02FB 825 W^RIOSAB_BUFFER ; Move text into global buffer
02FE 826
00000000'EF 16 02FE 827 JSB RIOSOUTPUT_LINE
43 50 E9 0304 828 BLBC R0,100$ ; Branch on error
0307 829
2628'CF 0064 8F B0 0307 830 70$: MOVW #100,W^OUTBUF ; Set full buffer length
00002614'EF 66 57 28 030E 831 MOVW R7,(R6),BOOSGT_SAVE_DEVNAME ; Save new devname
55 0000248C'EF 9E 0316 832 MOVAB BOOSAL_ACF,R5 ; Reset R5
031D 833 $FAO_S CTRSTR=CTRSTR_AUTOLOG,- ; Format device name
031D 834 OUTBUF=OUTBUF,-
031D 835 OUTLEN=OUTLEN,-
031D 836 P1=ACF$DEVNAME(R5),-
031D 837 P2=ACF$W_UNIT(R5)
262C'CF 2610'CF C0 033C 838 ADDL2 W^OUTLEN,W^OUTBUF+4 ; Add to descriptor
2628'CF 2610'CF A2 0343 839 SUBW2 W^OUTLEN,W^OUTBUF ; Subtract from length
034A 840 ; Return with FAO status
05 034A 841 100$: RSB
034B 842

```



```
034B 844 .SBTTL SGN$GET_DEVICE - Locate device database
034B 845
034B 846
034B 847 : Inputs:
034B 848 4(SP) - Address of Device name in ascic format
034B 849 8(SP) - Unit number
034B 850
034B 851 : Outputs:
034B 852 (Any of these are 0 if the data block doesn't exist)
034B 853 ACF$GL_DDB - Address of DDB
034B 854 ACF$GL_UCB - Address of UCB
034B 855 ACF$GL_IDB - Address of IDB
034B 856 ACF$GL_CRB - Address of CRB
034B 857 ACF$GL_SB - Address of SB
034B 858 ACF$GL_LASTDDB - If ACF$GL_DDB is non-zero, then equal to that,
034B 859 otherwise, last DDB in DEVLIST
034B 860 R0 = 0 - error
034B 861 = 1 - success
034B 862
034B 863 : Must be called at IPL=0 and KERNEL mode
034B 864
034B 865 .ENABL LSB
034B 866
034B 867 SGN$GET_DEVICE:: : Entry with IODB MUTEX & raised IPL
034B 868
007C 8F BB 034B 869 PUSH R2,R3,R4,R5,R6 : ADDS 20 to offset to input
54 00000000'GF D0 034F 870 :
32 10 034F 871 MOVL G^CTL$GL_PCB,R4 : PICK UP PCB POINTER
0356 872 BSBB 10$ : Call real routine
0358 873
007C 8F BA 0358 874 POP R2,R3,R4,R5,R6 : restore regs
05 035C 875 RSB : Return
035D 876
035D 877 SGN$GET_DEVICE_LOCK_IODB: : Entry without IODB MUTEX and IPL 0
035D 878
007C 8F BB 035D 879 PUSH R2,R3,R4,R5,R6 : ADDS 20 to offset to input
54 00000000'GF D0 0361 880 :
00000000'GF 16 0368 881 MOVL G^CTL$GL_PCB,R4 : PICK UP PCB POINTER
1A 10 036E 882 JSB G^SCH$IOLOCKR : GET THE IODB MUTEX FOR READ & RAISE IPL
50 DD 0370 883 BSBB 10$ :
54 00000000'GF D0 0370 884 PUSH R0 : SAVE RETURN STATUS
00000000'GF 16 0372 885 MOVL G^CTL$GL_PCB,R4 : PICK UP PCB POINTER
0379 886 JSB G^SCH$IOUNLOCK : RELEASE THE IODB MUTEX
037F 887 SETIPL #0 : LOWER IPL
0382 888
007C 8F BB 0382 889 POPL R0 : RESTORE RETURN STATUS FROM LOCAL ROUTINE
50 8ED0 0385 890 POP R2,R3,R4,R5,R6
05 0389 891 RSB
038A 892
2400'CF D4 038A 893 10$: CLRL W^ACF$GL_DDB : INIT TO ZERO
2404'CF D4 038E 894 CLRL W^ACF$GL_UCB : INIT TO ZERO
2408'CF D4 0392 895 CLRL W^ACF$GL_IDB : INIT TO ZERO
240C'CF D4 0396 896 CLRL W^ACF$GL_CRB : INIT TO ZERO
2418'CF D4 039A 897 CLRL W^ACF$GL_SB : INIT TO ZERO
039E 898
56 20 AE D0 039E 899 SAVIPL -(SP) : SAVE THE CURRENT IPL
03A1 900 MOVL 32(SP),R6 : GET ADDR OF DEVICE NAME
```

55	86	9A	03A5	901	MOVZBL	(R6)+,R5	:GET SIZE OF DEVICE NAME
7E	55	7D	03A8	902	MOVQ	R5,-(SP)	:FORM DESCRIPTOR
51	5E	D0	03AB	903	MOVL	SP,R1	:ADDRESS OF DESCRIPTOR
00000000	GF	16	03AE	904	JSB	G^IOC\$SEARCHALL	:SEARCH FOR DEVICE
	8E	7C	03B4	905	CLRQ	(SP)+	:GET RID OF TRASH
			03B6	906	SETIPL	(SP)+	:RESTORE OLD IPL
2418	CF	53	D0	03B9	MOVL	R3,W^ACF\$GL_SB	:STUFF THE SYSTEM BLOCK
		04	12	03BE	BNEQ	20\$	:NO ERROR, CONTINUE
		50	D4	03C0	CLRL	R0	:INDICATE ERROR
		5E	11	03C2	BRB	70\$	:EXIT
			03C4	911			
	0B	50	E8	03C4	BLBS	R0,25\$	:SUCCESS - FOUND DEVICE
0908	8F	50	B1	03C7	CMPW	R0,#SS\$_NOSUCHDEV	:CHECK IF ERROR WAS "UNIT NOT FOUND"
		36	12	03CC	BNEQ	60\$	:IF NOT, PUNT
		51	D5	03CE	TSTL	R1	:SEE IF WE GOT BACK A UCB ADDRESS
		32	12	03D0	BNEQ	60\$	:IF NON-ZERO, IS LISTHEAD - NO DDB FOUND
00002400	EF	52	D0	03D2	MOVL	R2,L^ACF\$GL_DDB	:ADDRESS OF DDB
54	04	A2	D0	03D9	MOVL	DDB\$L_UCB(R2),R4	:GET ADDRESS OF FIRST UCB
		25	13	03DD	BEQL	60\$	:IF NO UCB, EXIT WITH OTHER FIELDS ZERO
51	24	A4	D0	03DF	MOVL	UCB\$L_CRB(R4),R1	:GET ADDR OF CRB
0000240C	EF	51	D0	03E3	MOVL	R1,L^ACF\$GL_CRB	:SAVE
2408	CF	2C	A1	03EA	MOVL	CRB\$L_INTD+VEC\$L_IDB(R1),W^ACF\$GL_IDB	:GET ADDR OF IDB
			03F0	923			
54	A4	20	AE	B1	03F0	924	30\$: CMPW 32(SP),UCB\$W_UNIT(R4)
		08	13	03F5	925		:IS UCB ALREADY LOADED?
		54	30	A4	D0	03F7	926 40\$: BEQL 50\$
		F3	12	03FB	927		:BRANCH IF IT IS
		05	11	03FD	928		:GET ADDR OF NEXT UCB
			03FF	929			:BR IF THERE IS ONE
2404	CF	54	D0	03FF	930	50\$: MOVL R4,W^ACF\$GL_UCB	
00002410	EF	52	D0	0404	931	60\$: MOVL R2,ACF\$GL_LASTDDB	:LAST DDB IN LIST AS SEARCHED
50	00000000	GF	DE	040B	932	MOVAL G^SCS\$GA_LOCALSB,R0	:GET ADDRESS OF LOCAL SYSTEM BLOCK
		50	D1	0412	933	CMPPL R3,R0	:IS THIS SB LOCAL?
		08	13	0415	934	BEQL 65\$	:YES, LEAVE NOW
		18	A3	7D	0417	935	MOVQ SB\$B_SYSTEMID(R3),-
0000244C	EF			041A	936		L^BOO\$GQ_CONSYSID
				041F	937		:NO, SET IN THE SYSTEM ID
		50	01	D0	041F	938	65\$: MOVL #1,R0
			05	0422	939	70\$: RSB	:SUCCESS
				0423	940		
				0423	941		
				0423	942	.DSABL	LSB



```

0423 944 .SBTTL Reset routines BOO$RESETLIST and BOO$CONRESET and BOO$MSCP_RESET
0423 945 ;
0423 946 ; BOO$CONRESET - Reset values for connect command
0423 947 ;
0423 948 ;
00000200 949 .PSECT PAGED_CODE rd,nowrt,exe,long
0200 950
0000 0200 951 .Entry BOO$CONRESET, ^M<> ; Null entry mask
0202 952
0000245C'EF 00000200'EF 9E 0202 953 MOVAB L^BOO$AB_PRMBUF,BOO$GL_NEXTSTR ; Reset for string allocation
00002428'EF 01 CE 020D 954 MNEGL #1,BOO$GL_CONCREG ; Null control register
0000243C'EF 01 CE 0214 955 MNEGL #1,BOO$GL_CONAUNIT ; Null adapter unit
00002434'EF 01 CE 021B 956 MNEGL #1,BOO$GL_CONVECT ; Null vector
00002438'EF 01 D0 0222 957 MOVL #1,BOO$GL_CONNUMV ; Default number of vectors
00002424'EF 02 CE 0229 958 MNEGL #2,BOO$GL_CONADP ; Invalidate adapter TR value
00002440'EF D4 0230 959 CLRL BOO$GL_CONDEV ; Clear device name pointer
00002444'EF D4 0236 960 CLRL BOO$GL_CONDRV ; and driver name pointer
00002448'EF D4 023C 961 CLRL BOO$GL_CONUNITS ; and maximum units
0000244C'EF 7C 0242 962 CLRL BOO$GL_CONSYSID ; and system id
00002458'EF D4 0248 963 CLRL BOO$GL_CONFLAGS ; and flags
00002430'EF 01 D0 024E 964 MOVL #1,L^BOO$GL_CONNUMU ; Set number of units to 1
0000241C'EF D4 0255 965 CLRL BOO$GL_COMBO_VECTOR_OFFSET ; Set vector offset from combo vectors to
00002420'EF D4 025B 966 CLRL BOO$GL_COMBO_CSR_OFFSET ; Set CSR offset from combo CSR to 0
04 0261 967 RET ; Return
0262 968 ;
0262 969 ; BOO$RESETLIST - Reset select list values
0262 970 ;
0000 0262 971 .Entry BOO$RESETLIST, ^M<> ; Null entry mask
0264 972
0000245C'EF 00002460'EF D4 0264 973 CLRL BOO$GL_SELECT ; Zap select list pointer
00000200'EF 9E 026A 974 MOVAB BOO$AB_PRMBUF,BOO$GL_NEXTSTR ; Set next string address
00002614'EF D4 0275 975 CLRL BOO$GL_SAVE_DEVNAME ; Clear autolog string
00002610'EF D4 027B 976 CLRL OUTLEN ; Clear autolog output size
0000262C'EF 00002630'EF DE 0281 977 MOVAL OUTBUF_STR,OUTBUF+4 ; Set address in descriptor of block
00002497'EF 94 028C 978 CLRB BOO$AL_ACF+ACF$B_AFLAG ; Clear ACF flags
00002430'EF 01 D0 0292 979 MOVL #1,L^BOO$GL_CONNUMU ; Set number of units to 1
04 0299 980 RET ; and return
029A 981 ;
029A 982 ; BOO$MSCP_RESET - Reset the MSCP server initialization argument list
029A 983 ;
029A 984 ;
003C 029A 985 .Entry BOO$MSCP_RESET, ^M<R2,R3,R4,R5> ; Entry mask
029C 986
FF5F CF 00 FB 029C 987 CALLS #0,BOO$CONRESET ; Reset the connect command globals
50 0084 8F 3C 02A1 988 MOVZWL #SS$ DEVOFFLINE,R0 ; Assume error
00000000'GF D5 02A6 989 TSTL G^SCS$GL_CDL ; SCS loaded?
2C 13 02AC 990 BEQL 10$ ; If eql no, error
50 02C4 8F 3C 02AE 991 MOVZWL #SS$ DEVACTIONE,R0 ; Assume error
50 03 00 02 F0 02B3 992 INSV #2,#0,#3,R0 ; Set E class error status
00000000'GF D5 02B8 993 TSTL G^SCS$GL_MSCP ; If neq already loaded
1A 12 02BE 994 BNEQ 10$ ; Exit with error
00002444'GF 000025EC'EF DE 02C0 995 MOVAL MSCP_NAME,G^BOO$GL_CONDRV ; Set pointer to MSCP server name
30 28 02CB 996 MOVCL #MSCP_ARG_LIST_SIZE ; Set up default argument list for
000025BC'GF 0000258C'EF 02CD 997 MSCP_ARG_LIST,G^BOO$GL_LOAD_ARGS ; MSCP server init routine
50 01 D0 02D7 998 MOVL #1,R0 ; Set success
04 02DA 999 RET ; and return
02DB 1000

```



```

02DB 1001 :
02DB 1002 : BOO$MSCP_ARG - Load MSCP arguments
02DB 1003 :
0000 02DB 1004 .Entry BOO$MSCP_ARG, ^M<> ; Entry mask
02DD 1005 :
50 20 AC D0 02DD 1006 MOVL TPASL_PARAM(AP),R0 ; Get longword offset
1C AC D0 02E1 1007 MOVL TPASL_NUMBER(AP),- ; Load argument value
000025BC'GF40 02E4 1008 G^BOO$GL_LOAD_ARGS[R0]
50 01 D0 02EA 1009 MOVL #1,R0 ; Set success
04 02ED 1010 RET ; and return
02EE 1011 :
02EE 1012 :
02EE 1013 :
02EE 1014 : BOO$MAKLIST - Make a select list entry
02EE 1015 :
007C 02EE 1016 .Entry BOO$MAKLIST, ^M<R2,R3,R4,R5,R6> ; Entry mask
02F0 1017 :
56 0000245C'EF D0 02F0 1018 MOVL L^BOO$GL_NEXTSTR,R6 ; Get pointer to next available string space
00002460'EF D5 02F7 1019 TSTL L^BOO$GL_SELECT ; Is selection pointer already set
07 12 02FD 1020 BNEQ 10$ ; Yes, continue to add entry
00002460'EF 56 D0 02FF 1021 MOVL R6,L^BOO$GL_SELECT ; Else set pointer to first select entry
50 10 AC D0 0306 1022 10$: MOVL TPASL_TOKENCNT(AP),R0 ; Get string length
86 50 90 030A 1023 MOVB R0,(R6)+ ; Set count for string
66 14 BC 50 28 030D 1024 MOVC3 R0,@TPASL_TOKENPTR(AP),(R6) ; Copy string body
63 94 0312 1025 CLRB (R6) ; Mark end of list
0000245C'EF 53 D0 0314 1026 MOVL R3,L^BOO$GL_NEXTSTR ; Save next string address
50 01 D0 031B 1027 MOVL #1,R0 ; Set success status
04 031E 1028 RET

```



```
.SBTTL BOO$CONADP - Set connect adapter number

00002424'EF 1C AC 0000 031F 1030 .Entry BOO$CONADP, ^M<>
DO 031F 1031 MOVL TPASL_NUMBER(AP),L^BOO$GL_CONADP ; Set adapter number
04 0321 1033 RET ; and return
0329 1034
032A 1035
00002424'EF 01 0000 032A 1036 .Entry BOO$CONNLADP ^M<> ; Connect with null adapter
CE 032C 1037 MNEGL #1,L^BOO$GL_CONADP ; Clear adapter number
04 0333 1038 RET ; and return
0334 1039
0000 0334 1040 .Entry BOO$CONVECOFFSET, ^M<> ; Offset from start of combo vectors
1C AC DO 0336 1041 MOVL TPASL_NUMBER(AP),- ; Set offset value
0000241C'EF 04 0339 1042 L^BOO$GL_COMBO_VECTOR_OFFSET
033E 1043 RET ; and return
033F 1044
0000 033F 1045 .Entry BOO$CONCSROFFSET, ^M<> ; Offset from start of combo CSRs
1C AC DO 0341 1046 MOVL TPASL_NUMBER(AP),- ; Set offset value
00002420'EF 04 0344 1047 L^BOO$GL_COMBO_CSR_OFFSET
0349 1048 RET ; and return
034A 1049
00002428'EF 1C AC 0D 00 0000 034A 1050 .Entry BOO$CONCREG, ^M<> ; Control register address
EF 034C 1051 EXTZV #0,#13,TPASL_NUMBER(AP),L^BOO$GL_CONCREG; Set control register
04 0356 1052 RET ; and return
0357 1053
1C AC FFFFFFFE03 8F 0000 0357 1054 .Entry BOO$CONVEC, ^M<> ; Set controller vector
CB 0359 1055 BICL3 #^XFFFFFFE03,TPASL_NUMBER(AP),L^BOO$GL_CONVECT ; Set vector offset
00002434'EF 04 0366 1056 RET ; and return
0367 1057
00002438'EF 1C AC 0000 0367 1058 .Entry BOO$CONCNUM, ^M<> ; Number of vectors
DO 0369 1059 MOVL TPASL_NUMBER(AP),L^BOO$GL_CONNUMV ; Set number of vectors
04 0371 1060 RET ; and return
0372 1061
0000243C'EF 1C AC 0000 0372 1062 .Entry BOO$CONAUNIT, ^M<> ; Adapter unit number
DO 0374 1063 MOVL TPASL_NUMBER(AP),L^BOO$GL_CONAUNIT; Set adapter unit number
04 037C 1064 RET ; and return
037D 1065
007C 037D 1066 .Entry BOO$CONDRVNAM, ^M<R2,R3,R4,R5,R6> ; Entry mask (R2-R6)
037F 1067
56 0000245C'EF DO 037F 1068 MOVL L^BOO$GL_NEXTSTR,R6 ; Address of next string storage
00002444'EF 56 DO 0386 1069 MOVL R6,BOO$GL_CONDRV ; Save pointer to driver name
86 10 AC 90 038D 1070 MOVB TPASL_TOKENCNT(AP),(R6)+ ; Set count for string
0000245C'EF 56 10 AC C1 0391 1071 ADDL3 TPASL_TOKENCNT(AP),R6,BOO$GL_NEXTSTR ; Mark string allocated
66 14 BC 10 AC 28 039A 1072 MOVC3 TPASL_TOKENCNT(AP),@TPASL_TOKENPTR(AP),(R6) ; Copy string
50 01 DO 03A0 1073 MOVL #1,R0 ; and return success
04 03A3 1074 RET
03A4 1075
00FC 03A4 1076 .Entry BOO$DEVNAME, ^M<R2,R3,R4,R5,R6,R7> ; Device name/unit
03A6 1077
56 0000245C'EF DO 03A6 1078 MOVL BOO$GL_NEXTSTR,R6 ; Get pointer to next available string
54 14 AC DO 03AD 1079 MOVL TPASL_TOKENPTR(AP),R4 ; Get pointer to string
53 10 AC DO 03B1 1080 MOVL TPASL_TOKENCNT(AP),R3 ; And number of characters
00002588'EF D4 03B5 1081 CLRL FULL_NAME_PTR ; Initialize full device name
57 86 9E 03BB 1082 (R6)+,R7 ; Save pointer
64 53 24 3A 03BE 1083 LOCC #^A/$/,R3,(R4) ; Find any possible '$'
22 13 03C2 1084 BEQL 8$ ; None, just continue
00002588'EF 57 DO 03C4 1085 MOVL R7,FULL_NAME_PTR ; Store pointer
```



55	53	50	C3	03CB	1086	SUBL3	R0,R3,R5	:	Number of characters in node
67	55	01	81	03CF	1087	ADDB3	#1,R5,(R7)	:	Set in size (incl '\$')
		03	BB	03D3	1088	PUSHR	#^M<R0,R1>	:	Save registers
66	64	53	28	03D5	1089	MOVC3	R3,(R4),(R6)	:	Copy full string
	56	53	D0	03D9	1090	MOVL	R3,R6	:	Save ending address
		03	BA	03DC	1091	POPR	#^M<R0,R1>	:	Restore registers
53	50	01	C3	03DE	1092	SUBL3	#1,R0,R3	:	Number of characters left
54	51	01	C1	03E2	1093	ADDL3	#1,R1,R4	:	Pointer to string
	55	86	9E	03E6	1094	MOVAB	(R6)+,R5	:	Save pointer to count byte
		65	94	03E9	1095	CLRB	(R5)	:	Initialize count to zero
		52	D4	03EB	1096	CLRL	R2	:	Initialize unit accumulator
	50	84	9A	03ED	1097	MOVZBL	(R4)+,R0	:	Get a character from device name
	30	50	91	03F0	1098	CMPB	R0,#^A/0/	:	And check for a digit
		05	1F	03F3	1099	BLSSU	20\$	:	Branch if not
	39	50	91	03F5	1100	CMPB	R0,#^A/9/	:	Final check for digit
		0F	1B	03F8	1101	BLEQU	40\$	:	Yes it is
	86	50	90	03FA	1102	MOVB	R0,(R6)+	:	Part of device name
		65	96	03FD	1103	INCB	(R5)	:	Increase count
		67	96	03FF	1104	INCB	(R7)	:	Including nodename
	E9	53	F5	0401	1105	SOBGTR	R3,10\$	:	Continue
		16	11	0404	1106	BRB	50\$	:	
	50	84	9A	0406	1107	MOVZBL	(R4)+,R0	:	Get another digit
	50	30	C2	0409	1108	SUBL	#^A/0/,R0	:	Get value
	52	0A	C4	040C	1109	MULL	#10,R2	:	Scale accumulator before adding digit
		2F	19	040F	1110	BLSS	60\$	:	Error
	50	09	D1	0411	1111	CMPL	#9,R0	:	Check for numeric
		2A	19	0414	1112	BLSS	60\$	:	Error if not
	52	50	C0	0416	1113	ADDL	R0,R2	:	And add new digit
	EA	53	F5	0419	1114	SOBGTR	R3,30\$	:	Continue for entire unit number
0000245C'EF		56	D0	041C	1115	MOVL	R6,BOO\$GL_NEXTSTR	:	Save updated string pointer
0000242C'EF		52	D0	0423	1116	MOVL	R2,BOO\$GL_CONCUNIT	:	Set unit number
0000243C'EF		52	D0	042A	1117	MOVL	R2,BOO\$GL_CONAUNIT	:	Assume same for adapter unit
00002440'EF		55	D0	0431	1118	MOVL	R5,BOO\$GL_CONDEV	:	Save device name pointer
		65	95	0438	1119	TSTB	(R5)	:	Must not be null device name
		04	13	043A	1120	BEQL	60\$	:	Error if so
	50	01	D0	043C	1121	MOVL	#1,R0	:	Return success
			04	043F	1122	RET		:	and return
		50	D4	0440	1123	CLRL	R0	:	Return error status
			04	0442	1124	RET		:	
				0443	1125			:	
00002448'EF	1C	AC	0000	0443	1126	.Entry	BOO\$CONUNITS, ^M<>	:	Maximum units to be connected
			D0	0445	1127	MOVL	TPASL_NUMBER(AP),L^BOO\$GL_CONUNITS	:	Set maximum units
			04	044D	1128	RET		:	and return
				044E	1129			:	
0000244C'EF	1C	AC	0000	044E	1130	.Entry	BOO\$CONSYSID LOW, ^M<>	:	System ID
			D0	0450	1131	MOVL	TPASC_NUMBER(AP), -	:	Set System ID (low longword)
				0458	1132		L^BOO\$GQ_CONSYSID	:	and return
			04	0458	1133	RET		:	
				0459	1134			:	
00002450'EF	1C	AC	0000	0459	1135	.Entry	BOO\$CONSYSID HIGH, ^M<>	:	System ID
			D0	045B	1136	MOVL	TPASC_NUMBER(AP), -	:	Set System ID (high longword)
				0463	1137		L^BOO\$GQ_CONSYSID+4	:	and return
			04	0463	1138	RET		:	
				0464	1139			:	
			0000	0464	1140	.Entry	BOO\$CONSOLE, ^M<>	:	Connect console block stor. device
00002424'EF	01	CE		0466	1141			:	
				0466	1142	MNEGL	#1,L^BOO\$GL_CONADP	:	No adapter



SYSGEN  
V04-002

K 7  
- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00  
BOO\$CONADP - Set connect adapter number 14-SEP-1984 16:09:11 [BOOTS.SRC]SYSGEN.MAR;3

Page 26  
(4)

0000243C'EF	01	D0	046D	1143	MOVL	#1,L^BOO\$GL_CONAUNIT	; Set adapter unit = 1 (not used)
0000242C'EF	01	D0	0474	1144	MOVL	#1,L^BOO\$GL_CONCUNIT	; Set unit = 1
00002440'EF	000024D6'EF	9E	047B	1145	MOVAB	L^CONSNAME,L^BOO\$GL_CONDEV	; Set device name pointer
00002438'EF	02	D0	0486	1146	MOVL	#2,L^BOO\$GL_CONNUMV	; Set 2 vectors
00002428'EF		D4	048D	1147	CLRL	L^BOO\$GL_CONCREG	; No control register
00002430'EF	01	D0	0493	1148	MOVL	#1,L^BOO\$GL_CONNUMU	; Set number of units to 1
00002448'EF	02	D0	049A	1149	MOVL	#2,L^BOO\$GL_CONUNITS	; Set max units to 2 (OPA0 is 1st unit)
00000000'EF		16	04A1	1150	JSB	IOGEN\$CONSOLE	; Do cpu dependent stuff
50	01	D0	04A7	1151	MOVL	#1,R0	
		04	04AA	1152	RET		



```

04AB 1154 .SBTTL BOO$CONNECT - Connnect specified device and load driver
04AB 1155 :
04AB 1156 : BOO$CONNECT - Allows a single device to be introduced, appropriate data
04AB 1157 : structures allocated and initialized, the driver loaded if
04AB 1158 : required and the controller and device initialized.
04AB 1159 :
OFFC 04AB 1160 .Entry BOO$CONNECT, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ;
04AD 1161
FB50' 30 04AD 1162 BSBW BOO$LOCK_GEN ; Lock SYSGEN database
7F 50 E9 04B0 1163 BLBC R0,70$ ; If error, exit
04B3 1164
04B3 1165 : Value of BOO$GL_CONADP
04B3 1166 :
04B3 1167 : 0 or greater => /ADAPTER=n specified
04B3 1168 : -1 => /NOADAPTER specified
04B3 1169 : -2 => not specified
04B3 1170 :
04B3 1171 :
04B3 1172 :
00002424'EF D5 04B3 1173 5$: TSTL L^BOO$GL_CONADP ; Has an adapter been specified?
44 18 04B9 1174 BGEQ 20$ ; If so, branch
00002424'EF FFFFFFFF 8F D1 04BB 1175 CMPL #-1,L^BOO$GL_CONADP ; Null adapter?
28 13 04C6 1176 BEQL 10$ ; Branch if yes
00002424'EF FFFFFFFE 8F D1 04C8 1177 CMPL #-2,L^BOO$GL_CONADP ; None specified in CONNECT?
09 13 04D3 1178 BEQL 7$ ; Figure it out from the database
50 007C80D2 8F D0 04D5 1179 MOVL #SYSG$_NOADAPTER,R0 ; Set no adapter specified error
45 11 04DC 1180 BRB 60$ ; exit
04DE 1181
04DE 1182 7$: $CMKRNL_S W^CONN_ADAP ; Get adapter number from I/O database
35 50 E9 04EB 1183 BLBC R0,60$ ; Exit with error
C3 11 04EE 1184 BRB 5$ ; Dispatch now on adapter type
04F0 1185
04F0 1186 10$: $CMKRNL_S W^CONNADP ; Change mode to see data base
0D 11 04FD 1187 BRB -30$ ; Continue
04FF 1188
04FF 1189 20$: $CMKRNL_S W^CONNECT ; Change mode to see data base
00000000'EF 0E 50 E9 050C 1190 30$: BLBC R0,40$ ; Error occurred
0000248C'EF FA 050F 1191 CALLG L^BOO$AL_ACF,IOGEN$LOADER ; Load database and driver
03 50 E8 051A 1192 BLBS R0,50$ ; Branch if success
FAE0' 30 051D 1193 40$: BSBW PUTERROR ; Give error message
50 01 D0 0520 1194 50$: MOVL #1,R0 ; Set success for parser
50 DD 0523 1195 60$: PUSHL R0 ; Save error status
FAD8' 30 0525 1196 BSBW BOO$UNLOCK_GEN ; Unlock SYSGEN database
03 50 E8 0528 1197 BLBS R0,65$ ; If no error, continue
FAD2' 30 052B 1198 BSBW PUTERROR ; Give error message
50 8ED0 052E 1199 65$: POPL R0 ; Restore status
04 0531 1200 RET ;
FACB' 30 0532 1201 70$: BSBW PUTERROR ; Give error message
04 0535 1202 RET ;
0536 1203 :
0536 1204 : Local routine to get adapter number from I/O database
0536 1205 : Must be called by a CMKRNL since SGN$GET_DEVICE must be called
0536 1206 : in Kernel mode.
0536 1207 :
0000 0536 1208 .Entry CONN_ADAP, ^M<>
0538 1209
7E 0000242C'EF 3C 0538 1210 MOVZWL L^BOO$GL_CONCUNIT,-(SP) ; Unit number

```

	00002440'EF	DD	053F	1211	PUSHL	L^BOOS\$GL_CONDEV	; Device name
	0000035D'EF	16	0545	1212	JSB	SGN\$GET_DEVICE_LOCK_IODB	; Get device data base addresses
	5E 08	CO	054B	1213	ADDL2	#8,SP	; Pop off input parameters
			054E	1214			
50	00002408'EF	DO	054E	1215	MOVL	L^ACF\$GL_IDB,R0	; Address of IDB
	09	12	0555	1216	BNEQ	5\$	; Error if zero
50	007C80D2 8F	DO	0557	1217	MOVL	#SYSG\$_NOADAPTER,R0	; Set no adapter specified error
	18	11	055E	1218	BRB	20\$	; Branch to exit
			0560	1219			
	00002424'EF	01	CE	0560	1220	5\$: MNEGL	#1,L^BOOS\$GL_CONADP ; Assume null adapter
	50 14 A0	DO	0567	1221	MOVL	IDB\$L_ADP(R0),R0	; Address of ADP block
		13	056B	1222	BEQL	10\$	; Null adapter if zero
00002424'EF	0C A0	3C	056D	1223	MOVZWL	ADP\$W_TR(R0),L^BOOS\$GL_CONADP	; Set adapter number
			0575	1224			
	50 01	DO	0575	1225	10\$: MOVL	#1,R0	; Set success
		04	0578	1226	20\$: RET		; Return
			0579	1227			



```

0579 1229 .ENABL LSB
0579 1230 ; Connect with null adapter
0579 1231
OFFC 0579 1232 .Entry CONNLADP, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
057B 1233
50 00002588'EF D0 057B 1234 MOVL L^FULL_NAME_PTR,R0 ; Try full device name
07 12 0582 1235 BNEQ 5$ ; Good, continue
50 00002440'EF D0 0584 1236 MOVL L^BOO$GL_CONDEV,R0 ; Use normal name
5A 0000248C'EF 9E 058B 1237 5$: MOVAB L^BOO$AL_ACF,R10 ; Address ACF
6A D4 0592 1238 CLRL ACF$$_ADAPTER(R10) ; Set no adapter
04 AA D4 0594 1239 CLRL ACF$$_CONFIGREG(R10) ; Set address of config reg
08 AA B4 0597 1240 CLRW ACF$$_AVECTOR(R10) ; Set SCB offset for adapter
01 E1 059A 1241 BBC #ACF$$_CRBBLT,- ; Br. if CRB built flag is clear
4C 00002458'EF 059C 1242 BOO$GL_CONFLAGS,17$
6A 00002454'EF D0 05A2 1243 MOVL BOO$GL_CONCRB,ACF$$_ADAPTER(R10) ; Store CRB address
43 11 05A9 1244 BRB 17$ ; Join common code
05AB 1245
OFFC 05AB 1246 .Entry CONNECT, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ;
05AD 1247
5B FFFFFFFC'GF 9E 05AD 1248 MOVAB G^IOCSGL ADPLIST-ADP$$_LINK,R11 ; Get address of adapter list
5B 04 AB D0 05B4 1249 10$: MOVL ADP$$_LINK(R11),R11 ; Flink onward through adapter list
08 12 05B8 1250 BNEQ 15$ ; Continue if another adapter
50 007C80BA 8F D0 05BA 1251 MOVL #SYSG$_INVADAP,R0 ; Set invalid adapter error
04 05C1 1252 RET ; Return
05C2 1253
00002424'EF 0C AB B1 05C2 1254 15$: CMPW ADP$$_TR(R11),L^BOO$GL_CONADP ; Is this the specified TR?
E8 12 05CA 1255 BNEQ 10$ ; No, try another
5A 0000248C'EF 9E 05CC 1256 MOVAB L^BOO$AL_ACF,R10 ; Get address of ACF
6A 5B D0 05D3 1257 MOVL R11,ACF$$_ADAPTER(R10) ; Set address of ADP
04 AA 6B D0 05D6 1258 MOVL ADP$$_CSR(R11),ACF$$_CONFIGREG(R10) ; Set address of config reg
50 1C AB 00000000'GF C3 05DA 1259 SUBL3 G^EXESGL SCB,- ; Calculate offset into SCB of
05E3 1260 ADP$$_AVECTOR(R11),R0 ; adapter's interrupt vectors.
08 AA 50 B0 05E3 1261 MOVW R0,ACF$$_AVECTOR(R10) ; Store offset in ACF.
50 00002440'EF D0 05E7 1262 MOVL L^BOO$GL_CONDEV,R0 ; Device name
05EE 1263
14 AA 00002440'EF D0 05EE 1264 17$: MOVL BOO$GL_CONDEV,ACF$$_DEVNAME(R10); Set pointer to device name
05F6 1266
05F6 1267 ; Now try to get driver name from DDB if it exists and load BOO$GQ_CONSYSID
05F6 1268 ; if HSC device.
05F6 1269
7E 0000242C'EF 3C 05FD 1270 MOVZWL L^BOO$GL_CONCUNIT,-(SP) ; Unit number
50 DD 05FD 1271 PUSHL R0 ; Device name
0000035D'EF 16 05FF 1272 JSB SGN$GET_DEVICE_LOCK_IODB; Get device data base addresses
5E 08 C0 0605 1273 ADDL2 #8,SP ; Pop off input parameters
08 50 E8 0608 1274 BLBS R0,20$ ; All okay
50 007C9010 8F D0 060B 1275 MOVL #SYSG$_NODEV,R0 ; Set error code - 'Device not known'
04 0612 1276 RET ; Leave
0613 1277
00 00002458'EF 05 E2 0613 1278 20$: BBSS #ACF$$_GETDONE,-
0615 1279 L^BOO$GL_CONFLAGS,21$ ; Notify LOADER that GET was done
061B 1280
18 AA 00002444'EF D0 061B 1281 21$: MOVL BOO$GL_CONDRV,ACF$$_DRVNAME(R10); And driver name
31 14 0623 1282 BGTR 30$ ; Branch if driver specified
51 00002400'EF D0 0625 1283 MOVL ACF$$_GL_DDB,R1 ; DDB address
07 13 062C 1284 BEQL 25$ ; Branch if none
18 AA 24 A1 DE 062E 1285 MOVAL DDB$$_DRVNAME(R1),ACF$$_DRVNAME(R10) ; Address from DDB

```



```

21 11 0633 1286 BRB 30$ ; Branch around name hackery
      0635 1287
56 0000245C'EF D0 0635 1288 25$: MOVL L^BOOS$GL_NEXTSTR,R6 ; Get address of next free space
      18 AA 56 D0 063C 1289 MOVL R6,ACF$$_DRVNAME(R10) ; Set as driver name address
      86 08 90 0640 1290 MOVVB #8,(R6)+ ; Set count for string
66 52455649 52442020 8F 7D 0643 1291 MOVQ #^A/ DRIVER/,(R6) ; Set driver suffix
      51 14 AA D0 064E 1292 MOVL ACF$$_DEVNAME(R10),R1 ; Pointer to device name
      66 01 A1 B0 0652 1293 MOVW 1(R1),(R6) ; Form default driver name
      0656 1294
      0A AA 0000243C'EF 90 0656 1295 30$: MOVVB BOOS$GL_CONAUNIT,ACF$$_AUNIT(R10); Set adapter unit
      21 AA 00002430'EF 90 065E 1296 MOVVB L^BOOS$GL_CONNUMU,ACF$$_NUMUNIT(R10)
      0666 1297 ; Store number of units to configure
      0B AA 00002458'EF 90 0666 1298 MOVVB BOOS$GL_CONFLAGS,ACF$$_AFLAG(R10) ; Store flags
0000241C'EF 00002434'EF A1 066E 1299 ADDW3 BOOS$GL_CONVECT,BOOS$GL_COMBO_VECTOR_OFFSET,-;
      10 AA 0679 1300 ACF$$_VECTOR(R10) ; Set vector address
50 0000241C'EF 08 02 EF 067B 1301 EXTZV #2,#8,BOOS$GL_COMBO_VECTOR_OFFSET,R0; Save vector offset in longwords
      1F AA 50 90 0684 1302 MOVVB R0,ACF$$_COMBO_VECTOR_OFFSET(R10);
      0688 1303 ;
      0688 1304 ; Set up ACF$$_CONTRLREG - can either be UNIBUS CSR or address of CI
      0688 1305 ; System id.
      0688 1306 ;
      0000244C'EF D5 0688 1307 TSTL BOOS$GQ_CONSYSID ; See if SYSIDLOW was specified
      0A 13 068E 1308 BEQL 40$ ; Branch if not
      0C AA 0000244C'EF 9E 0690 1309 MOVAB BOOS$GQ_CONSYSID, -
      0698 1310 ACF$$_CONTRLREG(R10) ; Set system id address
      22 11 0698 1311 BRB 50$ ; Branch
      069A 1312 ;
      069A 1313 ; Calculate system virtual address of UNIBUS CSR
      069A 1314 ;
00002428'EF 00001000 8F C1 069A 1315 40$: ADDL3 #UBA_IOBASE, -
      0C AA 06A5 1316 BOOS$GL_CONCREG, -
      0C AA 04 AA C0 06A7 1317 ACF$$_CONTRLREG(R10) ; control register address
      00002420'EF C0 06A7 1318 ADDL ACF$$_CONFIGREG(R10), -
      0C AA 06AC 1319 ACF$$_CONTRLREG(R10) ; Add adapter va base
      00002420'EF C0 06AC 1320 ADDL BOOS$GL_COMBO_CSR_OFFSET,-; Add offset to get true CSR address
      0C AA 06B2 1321 ACF$$_CONTRLREG(R10) ;
      00002420'EF 8E 06B4 1322 MNEGB BOOS$GL_COMBO_CSR_OFFSET,-; Calculate offset back to CSR start
      20 AA 06BA 1323 ACF$$_COMBO_CSR_OFFSET(R10); Save offset
      06BC 1324
      12 AA 0000242C'EF B0 06BC 1325 50$: MOVW BOOS$GL_CONCUNIT, -
      06C4 1326 ACF$$_UNIT(R10) ; Set controller unit number
      1C AA 00002448'EF B0 06C4 1327 MOVW BOOS$GL_CONUNITS, -
      06CC 1328 ACF$$_MAXUNITS(R10) ; Set maximum units
      1E AA 00002438'EF 90 06CC 1329 MOVVB BOOS$GL_CONNUMV, -
      50 01 D0 06D4 1330 ACF$$_CONNUMV(R10) ; Set count of vectors
      04 06D7 1331 55$: MOVL #1,R0 ; Set success
      06D8 1332 ;
      06D8 1333 ;
      06D8 1334 ;
      06D8 1335 ;
      .DSABL LSB

```



		06D8	1337		.SBTTL	BOO\$LOAD - Load a driver or misc code if not already loaded
		06D8	1338	:		
		06D8	1339	:	BOO\$LOAD -	Loads the driver or misc code if not already loaded.
		06D8	1340	:		
	OFFC	06D8	1341	:	.Entry	BOO\$LOAD, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
		06DA	1342			
52	D4	06DA	1343		CLRL	R2 ; Clear reload flag
05	11	06DC	1344		BRB	LOADRV ; And merge with common code

```
06DE 1346 .SBTTL BOO$RELOAD - Reload a specified driver
06DE 1347 :
06DE 1348 : BOO$RELOAD - Reloads the specified driver replacing any existing copy
06DE 1349 : unless there are busy units requiring the driver that would
06DE 1350 : be replaced.
06DE 1351 :
06DE 1352 : Entry BOO$RELOAD, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ;
06E0 1353 :
52 01 90 06E0 1354 MOVB #ACF$M_RELOAD,R2 ; Set flag to force reload
06E3 1355 LOADRV:
06E3 1356 :
06E3 1357 : The first block of the file will be read to determine if it is a driver or
06E3 1358 : misc code by looking at the type field.
06E3 1359 :
00002444'EF DD 06E3 1360 PUSHL BOO$GL_CONDRV ; File name string
6E D6 06E9 1361 INCL (SP) ; Get past the count
7E 00002444'FF 9A 06EB 1362 MOVZBL @BOO$GL_CONDRV,-(SP) ; Length of file name
57 5E D0 06F2 1363 MOVL SP,R7 ; Address of descriptor for file name
F908' 30 06F5 1364 BSBW BOO$EXEOPEN ; Open the file (default SYSS$SYSTEM:.EXE)
5E 50 E9 06F8 1365 BLBC R0,40$ ; Error
5E 08 C0 06FB 1366 ADDL #8,SP ; Clean up stack
56 00002200'EF 9E 06FE 1367 MOVAB BOO$AB_LOADBUF,R6 ; Buffer for file read
58 02 D0 0705 1368 MOVL #2,R8 ; First block after image header
59 01 D0 0708 1369 MOVL #1,R9 ; One page
F8F2' 30 070B 1370 BSBW BOO$READFILE
48 50 E9 070E 1371 BLBC R0,40$ ; Error
F8EC' 30 0711 1372 BSBW BOO$FILCLOSE ; Close the currently open file
42 50 E9 0714 1373 BLBC R0,40$ ; Error
0000220A'EF 91 0717 1374 CMPB BOO$AB_LOADBUF+SLV$B_TYPE,-
62 8F 071D 1375 #DYN$C_LOADCODE ; Check for misc code
3C 13 071F 1376 BEQL LOADCODE
F8DC' 30 0721 1377 BSBW BOO$LOCK_GEN ; Lock SYSGEN database
32 50 E9 0724 1378 BLBC R0,40$ ; If lbc, didn't get lock
5A 0000248C'EF 9E 0727 1379 MOVAB L^BOO$AL_ACF,R10 ; Get base address for ACF block
18 AA 00002444'EF D0 072E 1380 MOVL BOO$GL_CONDRV,ACF$SL_DRVNAME(R10)
OB AA 52 90 0736 1381 MOVB R2,ACF$B_AFLAG(R10) ; Set flags for load or reload
14 AA D4 073A 1382 CLRL ACF$SL_DEVNAME(R10) ; No device name
00000000'EF 6A FA 073D 1383 CALLG (R10),L^IOGEN$LOADER ; Load requested driver
03 50 E8 0744 1384 BLBS R0,20$ ; Continue if no error
F8B6' 30 0747 1385 BSBW PUTERROR ; Give error message
50 DD 074A 1386 20$: PUSHL R0 ; Save status
F8B1' 30 074C 1387 BSBW BOO$UNLOCK_GEN ; Unlock SYSGEN database
03 50 E8 074F 1388 BLBS R0,30$ ; If no error, continue
F8AB' 30 0752 1389 BSBW PUTERROR ; Give error message
50 8ED0 0755 1390 30$: POPL R0 ; Restore status
04 0758 1391 RET ; Exit
F8A4' 30 0759 1392 40$: BSBW PUTERROR ; Give error message
04 075C 1393 RET ; Exit
075D 1394 :
075D 1395 : LOADCODE:
00002444'EF DD 075D 1396 PUSHL BOO$GL_CONDRV ; File name string
6E D6 0763 1397 INCL (SP) ; Get past the count
7E 00002444'FF 9A 0765 1398 MOVZBL @BOO$GL_CONDRV,-(SP) ; Length of file name
57 5E D0 076C 1399 MOVL SP,R7 ; Address of descriptor for file name
F88E' 30 076F 1400 BSBW BOO$UFOOPEN ; Open the file for user access (default SYS
22 50 E9 0772 1401 BLBC R0,10$ ; Error
5E 08 C0 0775 1402 ADDL #8,SP ; Clean up stack
```



```
00002200'EF 9F 0778 1403 PUSHAB BOO$AB_LOADBUF ; Use code buffer for return address array
          51 DD 077E 1404 PUSHL R1 ; Channel
          02 DD 0780 1405 PUSHL #2 ; Arg count
50 5E D0 0782 1406 MOVL SP,R0
          0785 1407 $CMKRNL_S ROUTIN = EXE$LOAD_CODE,-
          0785 1408 ARGST = (R0)
          04 50 E8 0794 1409 BLBS R0,20$
          F866' 30 0797 1410 10$: BSBW PUTERROR
          04 079A 1411 RET
          079B 1412
          079B 1413 20$: $CMKRNL_S ROUTIN = LINK_CODE
          EA 50 E9 07AA 1414 BLBC R0,10$
          04 07AD 1415 RET
          07AE 1416 ;
          07AE 1417 LINK_CODE:
          001C 07AE 1418 .WORD ^M<R2,R3,R4>
52 00002200'GF D0 07B0 1419 MOVL G^BOO$AB_LOADBUF,R2 ; Address of loaded code
          54 52 D0 07B7 1420 MOVL R2,R4 ; Save address of loaded code
          53 10 A4 D0 07BA 1421 MOVL SLV$A,SYSVECS(R4),R3 ; Get address of vectors in SYS.EXE
00000000'GF 16 07BE 1422 JSB G^EXE$LINK_VEC ; Connect vectors to loaded routines.
          10 50 E9 07C4 1423 BLBC R0,10$ ; Leave on error
5C 000025BC'GF DE 07C7 1424 MOVAL G^BOO$GL_LOAD_ARGS,AP ; Argument list for initialization routine
          50 04 A4 D0 07CE 1425 MOVL SLV$L_INITRTN(R4),R0 ; Possible initialization routine
          03 13 07D2 1426 BEQL 10$ ; None, leave
          6044 16 07D4 1427 JSB (R0)[R4] ; Call it
          04 07D7 1428 10$: RET
          07D8 1429
```

		07D8	1431	.SBTTL	BOO\$GIVEHELP - Print Help information	
		07D8	1432	:		
		07D8	1433	:	Print Help Information	
		07D8	1434	:		
003C		07D8	1435	.Entry	BOO\$GIVEHELP, ^M<R2,R3,R4,R5>	:
		07DA	1436			
00000000'GF	9F	07DA	1437	PUSHAB	G^LIB\$GET_INPUT	: Input routine
00002574'EF	9F	07E0	1438	PUSHAB	HELP_FLAG	: Flags
00002559'EF	9F	07E6	1439	PUSHAB	L^HELP_FILE	: Library
08 AC	B0	07EC	1440	MOVW	TPASL_STRINGCNT(AP),-	
00002578'EF		07EF	1441		HELP_DESC	: Set length
0C AC	D0	07F4	1442	MOVL	TPASC_STRINGPTR(AP),-	
0000257C'EF		07F7	1443		HELP_DESC+4	: Set address
00002578'EF	9F	07FC	1444	PUSHAB	HELP_DESC	: Input string
7E	D4	0802	1445	CLRL	-(SP)	: Width
00000000'GF	9F	0804	1446	PUSHAB	G^LIB\$PUT_OUTPUT	: Output routine
00000000'GF	06	FB	080A	CALLS	#6,G^LBR\$OUTPUT_HELP	: Call help routine
		0811	1448			
	04	0811	1449	RET		: Return with status
		0812	1450			
		0812	1451	.END		



SYSGEN  
Symbol table

- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00  
14-SEP-1984 16:09:11 [BOOTS.SRC]SYSGEN.MAR;3

Page 35  
(4)

\$ST1	= 00000001			BOO\$CONUNITS	00000443	RG	05
\$ST2	= 00000005			BOO\$CONVECOFFSET	00000334	RG	05
\$CLI.	= 00002464	R	04	BOO\$DEVNAME	000003A4	RG	05
\$CLI..	= 00002480	R	04	BOO\$EXEOPEN	*****	X	05
ACF\$B_AFLAG	= 0000000B			BOO\$FILCLOSE	*****	X	05
ACF\$B_AUNIT	= 0000000A			BOO\$FILOPEN	*****	X	05
ACF\$B_CNUMVEC	= 0000001E			BOO\$GB_FILELEN	000024FD	RG	04
ACF\$B_COMBO_CSR_OFFSET	= 00000020			BOO\$GIVEHELP	000007D8	RG	05
ACF\$B_COMBO_VECTOR_OFFSET	= 0000001F			BOO\$GL_CMDOPT	*****	X	06
ACF\$B_NUMUNIT	= 00000021			BOO\$GL_COMBO_CSR_OFFSET	00002420	RG	04
ACF\$C_LENGTH	= 00000028			BOO\$GL_COMBO_VECTOR_OFFSET	0000241C	RG	04
ACF\$GL_CRB	0000240C	RG	04	BOO\$GL_CONADP	00002424	RG	04
ACF\$GL_DDB	00002400	RG	04	BOO\$GL_CONAUNIT	0000243C	RG	04
ACF\$GL_DPT	00002414	RG	04	BOO\$GL_CONCRB	00002454	RG	04
ACF\$GL_IDB	00002408	RG	04	BOO\$GL_CONCREG	00002428	RG	04
ACF\$GL_LASTDDB	00002410	RG	04	BOO\$GL_CONCUNIT	0000242C	RG	04
ACF\$GL_SB	00002418	RG	04	BOO\$GL_CONDEV	00002440	RG	04
ACF\$GL_UCB	00002404	RG	04	BOO\$GL_CONDRV	00002444	RG	04
ACF\$SL_ADAPTER	= 00000000			BOO\$GL_CONFLAGS	00002458	RG	04
ACF\$SL_CONFIGREG	= 00000004			BOO\$GL_CONNUMU	00002430	RG	04
ACF\$SL_CONTRLREG	= 0000000C			BOO\$GL_CONNUMV	00002438	RG	04
ACF\$SL_DEVNAME	= 00000014			BOO\$GL_CONUNITS	00002448	RG	04
ACF\$SL_DRVNAME	= 00000018			BOO\$GL_CONVECT	00002434	RG	04
ACF\$M_RELOAD	= 00000001			BOO\$GL_DOT	*****	X	05
ACF\$V_CRBBLT	= 00000001			BOO\$GL_FILEADDR	000024F9	RG	04
ACF\$V_GETDONE	= 00000005			BOO\$GL_LOAD_ARGS	000025BC	RG	04
ACF\$V_NOLOAD_DB	= 00000003			BOO\$GL_NEXTSTR	0000245C	RG	04
ACF\$W_AVECTOR	= 00000008			BOO\$GL_PARINUSE	000024FE	RG	04
ACF\$W_CUNIT	= 00000012			BOO\$GL_RETSAVE	000024C4	RG	04
ACF\$W_CVECTOR	= 00000010			BOO\$GL_SELECT	00002460	RG	04
ACF\$W_MAXUNITS	= 0000001C			BOO\$GQ_CMDESC	= 0000246C	RG	04
ADP\$SL_AVECTOR	= 0000001C			BOO\$GQ_CONSYSID	0000244C	RG	04
ADP\$SL_CSR	= 00000000			BOO\$GQ_LIMITS	000024B4	RG	04
ADP\$SL_LINK	= 00000004			BOO\$GQ_RETADR	000024BC	RG	04
ADP\$W_TR	= 0000000C			BOO\$GT_ACTIVE	0000250A	RG	04
AUTOLOG	0000028F	RG	06	BOO\$GT_CURRENT	00002502	RG	04
BOO\$AB_LOADBUF	00002200	R	04	BOO\$GT_CVNAME	000024DE	RG	04
BOO\$AB_PATCH	00000000	RG	04	BOO\$GT_DDNAME	000024F0	RG	04
BOO\$AB_PRMBUF	00000200	RG	04	BOO\$GT_DEFAULT	00002511	RG	04
BOO\$AL_ACF	0000248C	RG	04	BOO\$GT_DXNAME	000024E7	RG	04
BOO\$AL_CLIBLK	00002464	RG	04	BOO\$GT_FILE	00002519	RG	04
BOO\$A_PRMBLK	*****	X	06	BOO\$GT_OPNAME	000024DA	RG	04
BOO\$CONADP	0000031F	RG	05	BOO\$GT_PROMPT	00002480	RG	04
BOO\$CONAUNIT	00000372	RG	05	BOO\$GT_SAVE_DEVNAME	00002614	R	04
BOO\$CONCNUM	00000367	RG	05	BOO\$GT_SYSPARNAME	*****	X	05
BOO\$CONCREG	0000034A	RG	05	BOO\$HICIM	00000000	RG	03
BOO\$CONCSROFFSET	0000033F	RG	05	BOO\$LOAD	000006D8	RG	05
BOO\$CONCVEC	00000357	RG	05	BOO\$LOCK_GEN	*****	X	06
BOO\$CONDRVNAM	0000037D	RG	05	BOO\$LOLIM	00000000	RG	02
BOO\$CONF IGALL	00000089	RG	06	BOO\$MAKLIST	000002EE	RG	05
BOO\$CONF IGONE	000000F8	RG	06	BOO\$MSCP_ARG	000002DB	RG	05
BOO\$CONNECT	000004AB	RG	05	BOO\$MSCP_RESET	0000029A	RG	05
BOO\$CONNLADP	0000032A	RG	05	BOO\$READFILE	*****	X	05
BOO\$CONRESET	00000200	RG	05	BOO\$RELOAD	000006DE	RG	05
BOO\$CONSOLE	00000464	RG	05	BOO\$RESETLIST	00000262	RG	05
BOO\$CONSYSID_HIGH	00000459	RG	05	BOO\$SEARCH	*****	X	05
BOO\$CONSYSID_LOW	0000044E	RG	05	BOO\$SENDOPER	00000140	RG	05



SYSGEN  
Symbol table

- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00  
14-SEP-1984 16:09:11 [BOOTS.SRC]SYSGEN.MAR;3

Page 36  
(4)

BOOSSETASCII	*****	X	05
BOOSSETVALUE	*****	X	05
BOOSUFOOPEN	*****	X	05
BOOSUNLOCK_GEN	*****	X	06
BOOSUSEACT	000000E9	RG	05
BOOSUSEFILE	00000000	RG	05
BOOSWRTACT	00000000	RG	06
BOOSWRTCUR	00000108	RG	05
BOOSWRTSYSPARFILE	*****	X	05
BOOCMDSV_AUTOLOG	= 0000000C		
BOOCMDSV_EXCLUDE	= 00000007		
BOOCMDSV_SELECT	= 00000006		
CLISB_RQTYPE	= 00000000		
CLISC_REQDESC	= 0000001C		
CLISK_GETCMD	= 00000001		
CLISW_RQSIZE	= 00000008		
CONFIGADP	0000018C	RG	06
CONFIG_EXIT	000000E6	R	06
CONNECT	000005AB	RG	05
CONNADP	00000579	RG	05
CONN ADAP	00000536	RG	05
CONSNAM	000024D6	R	04
CR	= 0000000D		
CRBSL_INTD	= 00000024		
CTL\$GL_PCB	*****	X	06
CTRSTR_AUTOLOG	000025F1	R	04
CTRSTR_AUTOLOG_UNIT	00002600	R	04
DDBSL_OCB	= 00000004		
DDBST_DRVNAME	= 00000024		
DONE	000000A9	R	05
DYN\$C_LOADCODE	= 00000062		
EXESA_SYSPARAM	*****	X	05
EXESC_SYSPARSZ	*****	X	05
EXESGL_DEFFLAGS	*****	X	06
EXESGL_DYNAMIC_FLAGS	*****	X	05
EXESGL_FLAGS	*****	X	06
EXESGL_SCB	*****	X	05
EXESGT_STARTUP	*****	X	05
EXESLINK_VEC	*****	X	05
EXESLOAD_CODE	*****	X	05
EXESV_NOAUTOCNF	*****	X	06
EXESV_WRITESYSPARAMS	*****	X	05
FACNAME	000024D0	R	04
FACNAMED	000024C8	RG	04
FACNAMSZ	= 00000006		
FF	= 0000000C		
FULL_NAME_PTR	00002588	RG	04
HELP_DESC	00002578	R	04
HELP_FILE	00002559	R	04
HELP_FLAG	00002574	R	04
HLP\$M_PROMPT	= 00000001		
IDBSL_ADP	= 00000014		
IOCSAUTOCONFIG	*****	X	06
IOCSAUTORESET	*****	X	06
IOCSGL_ADPLIST	*****	X	06
IOCSSEARCHALL	*****	X	06
IOGEN\$CONSOLE	*****	X	05

IOGEN\$LOADER	*****	X	06
IPL\$SCHED	= 00000003		
JPI\$-PID	= 00000319		
LBR\$OUTPUT_HELP	*****	X	05
LF	= 0000000A		
LIB\$GET_INPUT	*****	X	05
LIB\$PUT_OUTPUT	*****	X	05
LINK_CODE	000007AE	R	05
LOADCODE	0000075D	R	05
LOADRV	000006E3	R	05
LOCADP	00000163	R	06
MMGSA_SYSPARAM	*****	X	05
MSCP_ARG_LIST	0000258C	R	04
MSCP_ARG_LIST_SIZE	= 00000030		
MSCP_NAME	000025EC	R	04
NAMS\$RSL	*****	X	05
NAM\$RSL	*****	X	05
NEXTADP	0000013B	R	06
OPCSL_MS_TEXT	= 00000008		
OPCSM-NM-CENTRL	= 00000001		
OPCS_RQ_RQST	= 00000003		
OPERGETJPI	00002694	R	04
OPERMSG	000026C0	R	04
OPERMSGBUF	000026C8	R	04
OPERMSGFAO	000026AC	R	04
OPERMSGID	000026A8	R	04
OPERMSGNAM	000026B4	R	04
OPERMSGPID	000026B0	R	04
OPERMSGTXT	000026D0	R	04
OPERMSGVEC	000026A4	R	04
OPERNAMDESC	000026B8	R	04
OUTBUF	00002628	R	04
OUTBUF_STR	00002630	R	04
OUTLEN	00002610	R	04
OUTLEN_UNIT	0000260C	R	04
PR\$IPC	= 00000012		
PRMSB_POS	= 00000015		
PRMSB_SIZE	= 00000014		
PRMSC_LENGTH	= 00000032		
PRMSL_ADDR	= 00000000		
PRMSL_FLAGS	= 00000010		
PRMSM_DYNFLAGS	*****	X	06
PRMSV_ASCII	= 00000010		
PRMSV_DYNAMIC	= 00000000		
PUTERROR	*****	X	06
RIOSAB_BUFFER	*****	X	06
RIOSGW_OUTLEN	*****	X	06
RIOSOUTPUT_LINE	*****	X	06
RIO_INPNAM	*****	X	05
SAVE_DOT	00002584	R	04
SB\$B_SYSTEMID	= 00000018		
SCH\$IOLOCKR	*****	X	06
SCH\$IOUNLOCK	*****	X	06
SCSSGA_LOCALSB	*****	X	06
SCSSGL_CDL	*****	X	05
SCSSGL_MSCP	*****	X	05
SELECT	0000025A	R	06



SYSGEN  
Symbol table

- SYSGEN UTILITY AND PARAMETER FILE EDIT 16-SEP-1984 00:13:54 VAX/VMS Macro V04-00  
14-SEP-1984 16:09:11 [BOOTS.SRC]SYSGEN.MAR;3

Page 37  
(4)

SGNSGET_DEVICE	0000034B	RG	06
SGNSGET_DEVICE_LOCK_IODB	0000035D	R	06
SLVSA_SYSVECS	= 00000010		
SLVSB_TYPE	= 0000000A		
SLVSL_INITRTN	= 00000004		
SS\$DEVACTIVE	= 000002C4		
SS\$DEVOFFLINE	= 00000084		
SS\$NOPRIV	= 00000024		
SS\$NORMAL	= 00000001		
SS\$NOSUCHDEV	= 00000908		
SYS\$CMEXEC	*****	GX	06
SYS\$CMKRN	*****	GX	06
SYS\$FAO	*****	X	06
SYS\$GETJPI	*****	GX	05
SYS\$PUTMSG	*****	GX	05
SYS\$SNDOPR	*****	GX	05
SYS\$S_CONFQUAL	= 007C808A		
SYS\$S_INVADAP	= 007C80BA		
SYS\$S_NOADAPTER	= 007C80D2		
SYS\$S_NOAUTOCNF	= 007C8002		
SYS\$S_NODEV	= 007C9010		
SYS\$S_NOTPARAM	= 007C80EA		
SYS\$S_WRITEACT	= 007CA013		
SYS\$S_WRITECUR	= 007CA01B		
TPASL_NUMBER	= 0000001C		
TPASL_PARAM	= 00000020		
TPASL_STRINGCNT	= 00000008		
TPASL_STRINGPTR	= 0000000C		
TPASL_TOKENCNT	= 00000010		
TPASL_TOKENPTR	= 00000014		
UBA_IOWASE	= 00001000		
UCBSL_CRB	= 00000024		
UCBSL_LINK	= 00000030		
UCBSW_UNIT	= 00000054		
VALID_PAR_FILE	00002580	R	04
VECSL_IDB	= 00000008		

-----  
! Psect synopsis !  
-----

PSECT name	Allocation	PSECT No.	Attributes
. ABS .	00000000 ( 0.)	00 ( 0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$ABSS	00000000 ( 0.)	01 ( 1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
\$\$\$000	00000000 ( 0.)	02 ( 2.)	NOPIC USR CON REL LCL NOSHR NOEXE RD NOWRT NOVEC BYTE
222	00000000 ( 0.)	03 ( 3.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC PAGE
NONPAGED DATA	000027D0 (10192.)	04 ( 4.)	NOPIC USR CON REL LCL NOSHR NOEXE RD WRT NOVEC QUAD
PAGED CODE	00000812 ( 2066.)	05 ( 5.)	NOPIC USR CON REL LCL NOSHR EXE RD NOWRT NOVEC LONG
NONPAGED_CODE	00000423 ( 1059.)	06 ( 6.)	NOPIC USR CON REL LCL NOSHR EXE RD NOWRT NOVEC LONG

-----  
! Performance indicators !  
-----

Phase	Page faults	CPU Time	Elapsed Time
-----	-----	-----	-----
Initialization	37	00:00:00.09	00:00:00.49
Command processing	138	00:00:00.74	00:00:03.19
Pass 1	573	00:00:24.19	00:00:47.20
Symbol table sort	0	00:00:03.72	00:00:06.05
Pass 2	296	00:00:05.60	00:00:13.47
Symbol table output	31	00:00:00.26	00:00:00.27
Psect synopsis output	4	00:00:00.04	00:00:00.05
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	1081	00:00:34.65	00:01:10.73

The working set limit was 2000 pages.  
137940 bytes (270 pages) of virtual memory were used to buffer the intermediate code.  
There were 130 pages of symbol table space allocated to hold 2287 non-local and 103 local symbols.  
1451 source lines were read in Pass 1, producing 130 object records in Pass 2.  
50 pages of virtual memory were used to define 47 macros.

-----  
! Macro library statistics !  
-----

Macro library name	Macros defined
-----	-----
_\$255\$DUA28:[BOOTS.OBJ]BOOTS.MLB;1	1
_\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	18
_\$255\$DUA28:[SYSLIB]STARLET.MLB;2	25
TOTALS (all libraries)	44

2422 GETS were required to define 44 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:SYSGEN/OBJ=OBJ\$:SYSGEN MSRC\$:SYSGEN/UPDATE=(ENH\$:SYSGEN)+EXECML\$/LIB+LIB\$:BOOTS.MLB/LIB



0041 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY